

KINTEK SOLUTION

Cvd Materials Catalog

Contact us for more catalogs of Sample Preparation, Thermal Equipment, Lab Consumables & Materials, Bio-Chem Equipment, etc...



KINTEK SOLUTION

COMPANY PROFILE

>>> About Us

Kintek Solution Ltd is one technology orientated organization, team members are devoted to probing the most efficieent and reliable technology and innovations in the scienticfic researching equipment, fields like biochemical reacting, new materials researching, heat treatment, vaccum creating, refrigerating, as while as pharmaceutical and petroleum extracting equipment.

In the past 20 years, we earned rich experiences in this researing equipment field, we are capable to supply both the equipment and solution according to customer's needs and realities, we have also developed lots of customer tailer equipment accoding to a specific working purpose, and we have lots of successful projects in many universities and institutes from different countries, like Asia, Europe, North and south America, Australia and New Zealand, middle east, and Africa.

Profession, quick response, hard working, and sincerity is a remarkable label of our team meambers working attitude, which earn us a sound reputation among our clients.

We are here and ready to service our clients from different countries and regions, and share the most efficent and reliable technology together!





Cvd Diamond For Dressing Tools

Item Number: cvdm-01



Introduction

Experience the Unbeatable Performance of CVD Diamond Dresser Blanks: High Thermal Conductivity, Exceptional Wear Resistance, and Orientation Independence.

THICKNESS	WIDTH	LENGTH
0.3	0.3	3.0
0.4	0.4	2.0
0.4	0.4	3.0
0.4	0.4	5.0
0.5	0.5	2.0
0.5	0.5	3.0
0.5	0.5	5.0
0.6	0.6	2.0
06	0.6	3.0
0.6	0.6	5.0
0.8	0.8	0.8
0.8	0.8	1.5
0.8	0.8	3.0
0.8	0.8	4.0
0.8	0.8	5.0
1.0	1.0	1.0
1.0	1.0	3.0
1.0	1.0	4.0
1.0	1.0	5.0
1.5	1.5	1.5
1.5	1.5	3.0
1.5	3.0	3.0
1.5	3.0	3.5
1.5	3.0	4.0
1.5	4.0	4.0
1.8	1.8	1.8



3.5 1.8 3.0 1.8 3.5 3.5



Cvd Diamond For Thermal Management

Item Number: cvdm-02



Introduction

CVD diamond for thermal management: Highquality diamond with thermal conductivity up to 2000 W/mK, ideal for heat spreaders, laser diodes, and GaN on Diamond (GOD) applications.

Thermal Grade:	I
Thermal conductivity level:	1
Standard Medium:	>1200W/m.k
High:	>1500W/m.k
Excellent:	>1800W/m.k (up to 2000W/m.k)
Tolerance of Thickness:	±25um
Flatness:	
Density:	3.5g/cm³
Young's modulus:	1000-1100GPa
Growth side surface finish:	
Nucleation side surface finish:	
Standard Sizes	
Double sides polished :	Up to diameter 150 mm
As grown thickness:	Between 0.3 mm and 1.5 mm
Polished thickness:	Between 0.2 mm and 1.0 mm



Cvd Diamond Wire Drawing Die Blanks

Item Number: cvdm-03



Introduction

CVD diamond wire drawing die blanks: superior hardness, abrasion resistance, and applicability in wire drawing various materials. Ideal for abrasive wear machining applications like graphite processing.

Learn More

Product Number	Diameter of Inner Circle(mm)	Thickness(mm)
CVDD2010	2.0	1.0
CVDD2512	2.5	1.2
CVDD3015	3.0	1.5
CVDD4020	4.0	2.0

Note: The shapes mentioned above are hexangular.

Special specifications are available on request.

Parameters of properties

Vickers hardness	7000-10000kg/mm2
Density	3.51g/cm3
Young's modulus	1000-1100GPa
Thermal conductivity	>1000W/m.K
Chemical stability	insoluble in alkali and acid



Cutting Tool Blanks

Item Number: cvdm-04



Introduction

CVD Diamond Cutting Tools: Superior Wear Resistance, Low Friction, High Thermal Conductivity for Non-Ferrous Materials, Ceramics, Composites Machining



Cvd Diamond Coating

Item Number: cvdm-05



Introduction

CVD Diamond Coating: Superior Thermal Conductivity, Crystal Quality, and Adhesion for Cutting Tools, Friction, and Acoustic Applications

Vickers hardness:	8000-10000mm2
Young's Modulus:	1000-1100GPa
Friction Coefficient:	0.05-0.1
Thickness:	
Thickness after polishing:	



Cvd Diamond Domes

Item Number: cvdm-06




Introduction

Discover CVD diamond domes, the ultimate solution for high-performance loudspeakers. Made with DC Arc Plasma Jet technology, these domes deliver exceptional sound quality, durability, and power handling.



Cvd Boron Doped Diamond

Item Number: cvdm-07



Introduction

CVD boron-doped diamond: A versatile material enabling tailored electrical conductivity, optical transparency, and exceptional thermal properties for applications in electronics, optics, sensing, and quantum technologies.

Available dimension:	Diameter100mm, thickness 0.3-2mm
Boron Concentration [B]:	2 to 6×1020 Atoms /cm3, averaged over 0.16 mm2
Bulk Resistivity (Rv):	2 to 1.8 x 10-3 Ohm m, \pm 0.25 x 10-3 Ohm m
Solvent Window:	>3.0V



Optical Windows

Item Number: cvdm-08



Introduction

Diamond optical windows: exceptional broad band infrared transparency, excellent thermal conductivity & low scattering in infrared, for high-power IR laser & microwave windows applications.

Diameter:	65mm (F150mm on request)
thickness:	1mm
Flatness:	4um/cm
With higher transparency	
Thickness:	□0.3mm
Size:	20 diameter





Kintek Solution

Head Quarter: No.89 Science Avenue, High-Tech Zone,

Zhengzhou, China

Hongkong Office: 300 Lockhart Road, Wan Chai,

Hongkong

Canada Offce: Boulevard Graham, Mont-Royal, QC, H3P

2C7, Canada

