



KINTEK SOLUTION

## Electrochemical Consumables Catalog

Contact us for more catalogs of [Sample Preparation](#), [Thermal Equipment](#), [Lab Consumables & Materials](#), [Bio-Chem Equipment](#), etc...

# KINTEK SOLUTION

## COMPANY PROFILE

### >>> About Us

Kintek Solution Ltd is one technology orientated organization, team members are devoted to probing the most efficient and reliable technology and innovations in the scientific researching equipment, fields like biochemical reacting, new materials researching, heat treatment, vacuum creating, refrigerating, as well as pharmaceutical and petroleum extracting equipment.

In the past 20 years, we earned rich experiences in this researching equipment field, we are capable to supply both the equipment and solution according to customer's needs and realities, we have also developed lots of customer tailored equipment according to a specific working purpose, and we have lots of successful projects in many universities and institutes from different countries, like Asia, Europe, North and South America, Australia and New Zealand, Middle East, and Africa.

Profession, quick response, hard working, and sincerity is a remarkable label of our team members working attitude, which earn us a sound reputation among our clients.

We are here and ready to service our clients from different countries and regions, and share the most efficient and reliable technology together!



# Electrolytic Cell With Five-Port

Item Number: ELC



## Introduction

Streamline your laboratory consumables with Kintek's Electrolytic Cell with five-port design. Choose from sealed and non-sealed options with customizable electrodes. Order now.

[Learn More](#)

Specification	10ml~1000ml
Applicable temperature range	0~60°C
Sealed form	Thread / Apron
Material	Boron glass, PTFE
Openings in the electrolytic cell	Three electrode holes (6mm) and Two air holes (3mm), can be customized
Specification	10ml~1000ml
Applicable temperature range	0~60°C
Material	Boron glass, PTFE
Openings in the electrolytic cell	Three electrode holes (6mm), can be customized

## H Type Electrolytic Cell - H Type / Triple

Item Number: ELCH



### Introduction

Experience versatile electrochemical performance with our H-type Electrolytic Cell. Choose from membrane or non-membrane sealing, 2-3 hybrid configurations. Learn more now.

[Learn More](#)

Specification	30ml~ 500ml
Applicable temperature range	0 ~ 60°C
Applicable membrane area	15mm (can be customized)
Material	Boron glass + PTFE
Electrolytic cell punching	Three electrode holes (6mm) Four gas (3mm) can be customized opening

Specification	30ml~ 500ml
Applicable temperature range	0 ~ 60°C
Applicable membrane area	0.5cm <sup>2</sup> /1cm <sup>2</sup>
Material	Boron glass + PTFE
Electrolytic cell punching	Three electrode holes (6mm) Six air holes (3mm) can be customized

## Ptfe Electrolytic Cell Corrosion-Resistant Sealed / Non-Sealed

Item Number: ELCP



### Introduction

Choose our PTFE Electrolytic Cell for reliable, corrosion-resistant performance. Customize specifications with optional sealing. Explore now.

[Learn More](#)

Specification	10ml ~ 1000ml
Applicable temperature range	0 ~ 60°C
Sealed form	thread + apron
Material	PTFE
Electrolytic cell punching	Three electrode holes (6mm), two air holes (3mm), custom openings are available
Specification	10ml ~ 1000ml
Applicable temperature range	0 ~ 60°C
Material	PTFE
Electrolytic cell punching	Three electrode holes (6mm), custom openings are available

# Multifunctional Electrolytic Cell Water Bath Single Layer / Double Layer

Item Number: ELCM



## Introduction

Discover our high-quality Multifunctional Electrolytic Cell Water Baths. Choose from single or double-layer options with superior corrosion resistance. Available in 30ml to 1000ml sizes.

[Learn More](#)

Specification	30ml ~ 1000ml
Applicable temperature range	0 ~ 60°C
Material	Glass + PTFE
Working conductive sheet material	Copper / Titanium

## Water Bath Electrolytic Cell - Double Layer Five-Port

Item Number: ELCW



### Introduction


Experience optimal performance with our Water Bath Electrolytic Cell. Our double-layer, five-port design boasts corrosion resistance and longevity. Customizable to fit your specific needs. View specs now.

[Learn More](#)

Specification	50ml ~ 500ml
Applicable temperature range	0 ~ 60°C
Sealed form	Thread + Apron
Material	Boron glass + PTFE
Electrolytic cell hole	Three electrode holes (6mm), two air holes (3mm), custom openings are available

## Gas Diffusion Electrolysis Cell Liquid Flow Reaction Cell

Item Number: ELCG



### Introduction

Looking for a high-quality gas diffusion electrolysis cell? Our liquid flow reaction cell boasts exceptional corrosion resistance and complete specifications, with customizable options available to suit your needs. Contact us today!

[Learn More](#)

Airway type	snake-shaped airway / back-shaped airway / special-shaped custom
Cell material	optional PTFE / PEEK / PP / plexiglass / nylon



## Super Sealed Electrolytic Cell

Item Number: ELCS



### Introduction

Super-sealed electrolytic cell offers enhanced sealing capabilities, making it ideal for experiments that require high airtightness.

[Learn More](#)

Specification	30ml ~ 1000ml
Applicable temperature range	0 ~ 60°C
Sealed form	Thread + Apron
Material	Boron glass + PTFE
Electrolytic cell hole	Three electrode holes (6mm), two air holes (3mm), custom openings are available

## Water Bath Electrolytic Cell - H-Type Double-Layer Optical

Item Number: ELCHD



### Introduction

Double-layer H-type optical water bath electrolytic cells, with excellent corrosion resistance and a wide range of specifications available. Customization options are also available.

[Learn More](#)

Specification	10ml ~ 1000ml
Applicable temperature range	0 ~ 60°C
Sealed form	Thread + Apron
Material	Boron glass + PTFE
Electrolytic cell hole	Three electrode holes (6mm), two air holes (3mm), custom openings are available

# Double-Layer Water Bath Electrolytic Cell

Item Number: ELCWD



## Introduction

Discover the temperature-controllable electrolytic cell with a double-layer water bath, corrosion resistance, and customization options. Complete specifications included.

[Learn More](#)

Specification	50ml ~ 250ml
Applicable temperature range	0 ~ 60°C
Sealed form	Thread + Apron
Material	Boron glass + PTFE
Electrolytic cell hole	Three electrode holes (6mm), two air holes (3mm), custom openings are available
Specification	50ml ~ 500ml
Applicable temperature range	0 ~ 60°C
Material	Boron glass + PTFE
Electrolytic cell hole	Three electrode holes (6mm), custom openings are available

## Rotating Disk Electrode / Rotating Ring Disk Electrode (Rrde)

Item Number: ELER



### Introduction

Elevate your electrochemical research with our Rotating Disk and Ring Electrodes. Corrosion resistant and customizable to your specific needs, with complete specifications.

[Learn More](#)

Specifications	5mm gold/platinum/glassy carbon
Applicable temperature range	10 ~ 25°C
Purity	99.99%
Guide material	glassy carbon + platinum ring
Disk electrode material	glassy carbon/gold/platinum/graphite/zinc/nickel copper/iron, etc.
Jacket material	polytetrafluoroethylene (PTFE) / polysulfone (PEEK)
Collection rate	37%
Disk area	0.2475 cm <sup>2</sup>
Ring area	0.1866 cm <sup>2</sup>
Platinum ring outer diameter	7.92 mm
Platinum ring inner diameter	6.25 mm

# Optical Water Bath Electrolytic Cell

Item Number: ELCWO



## Introduction

Upgrade your electrolytic experiments with our Optical Water Bath. With controllable temperature and excellent corrosion resistance, it's customizable for your specific needs. Discover our complete specifications today.

[Learn More](#)

Specifications	50ml ~ 250ml
Applicable temperature range	0 ~ 60°C
Sealing form	Thread + Apron
Material	boron glass + PTFE
Electrolytic cell opening	three electrode holes (6mm), two air holes (3mm), can be customized
Specifications	50ml ~ 250ml
Applicable temperature range	0 ~ 60°C
Material	boron glass + PTFE
Electrolytic cell opening	three electrode holes (6mm), can be customized

# Electrode Fixture

Item Number: ELEF



## Introduction

Upgrade your experiments with our customizable Electrode Fixtures. High-quality materials, acid and alkali resistant, and safe and durable. Discover our complete models today.

[Learn More](#)

Features	Corrosion Resistant
Applicable temperature range	0 ~ 60°C
Clamping thickness	0.1 ~ 5mm
Material	PTFE rod + platinum sheet
Two built-in 10*10 and 10*15 (can be customized to clamp 10mm samples)	
Features	Corrosion Resistant
Applicable temperature range	0 ~ 60°C
Clamping thickness	0.1 ~ 5mm
Material	PTFE rod + gold sheet
Built-in 10*10 (can be customized clip 10mm sample)	
Features	Resistant to slight corrosion
Applicable temperature range	0 ~ 60°C
Clamping thickness	0.1 ~ 5mm
Material	PTFE rod + titanium sheet
Built-in 10*15 pieces (can be customized to clip 10mm samples)	
Features	Samples can be placed in parallel
Applicable temperature range	0 ~ 60°C
Clamping thickness	0.1 ~ 3mm
Material	PTFE rod + platinum sheet
Built-in 10*10 platinum sheet (can be made of gold sheet, sheet, copper sheet, etc.)	
Features	Easy to operate
Applicable temperature range	0 ~ 60°C
Clamping thickness	0.1 ~ 3mm
Material	PTFE Rod + Alligator Clip

The chuck is made of crocodile clips, easy to use and easy to operate

Features	High temperature resistance and slight corrosion resistance
----------	---

Applicable temperature range	0 ~ 80°C
------------------------------	----------

Clamping thickness	0.1 ~ 3mm
--------------------	-----------

Material	PEEK Rod + Platinum Sheet
----------	---------------------------

Built-in  $\phi$ 7mm platinum sheet (can be made of gold sheet, sheet, copper sheet, etc.)

Features	High temperature resistance and slight corrosion resistance
----------	---

Applicable temperature range	0 ~ 80°C
------------------------------	----------

Clamping thickness	0.1 ~ 3mm
--------------------	-----------

Material	PEEK Rod + Platinum Sheet
----------	---------------------------

Built-in 10\*10 platinum sheet (can be made of gold sheet, sheet, copper sheet, etc.)

Features	Can effectively inhibit the hydrogen evolution reaction
----------	---

Applicable temperature range	0 ~ 65°C
------------------------------	----------

Clamping thickness	0.1 ~ 3mm
--------------------	-----------

Material	PEEK Rod + Glassy Carbon
----------	--------------------------

Built-in 3mm imported glass carbon (note that the working voltage should not exceed 1A)

Features	High temperature resistance and slight acid and alkali resistance
----------	---

Applicable temperature range	0 ~ 80°C
------------------------------	----------

Clamping thickness	0.1 ~ 3mm
--------------------	-----------

Material	PEEK Rod + Platinum
----------	---------------------

Built-in 6\*6 and 9\*9 platinum sheets (can be customized variable diameter electrode clip 6 to 10)

Features	Can make the sample parallel
----------	------------------------------

Applicable temperature range	0 ~ 65°C
------------------------------	----------

Clamping thickness	0.1 ~ 3mm
--------------------	-----------

Material	PEEK Rod + Glassy Carbon
----------	--------------------------

Built-in 9\*9 platinum sheet (custom gold sheet, sheet, copper sheet material)

Features	Ultra-high temperature resistant and not acid resistant
----------	---

Applicable temperature range	0 ~ 200°C
------------------------------	-----------

Clamping thickness	0.1 ~ 3mm
--------------------	-----------

Material	316L stainless steel
----------	----------------------

Stainless steel is alkali-resistant, but not acid-resistant, so attention should be paid to the nature of the electrolyte

Features	Ultra-high temperature resistant Slight corrosion temperature range
----------	---

Applicable temperature range	0 ~ 200°C
------------------------------	-----------

Clamping thickness	0.1 ~ 3mm
--------------------	-----------

Material	Copper
----------	--------

Stainless steel is alkali-resistant, but not acid-resistant, so attention should be paid to the nature of the electrolyte

Features	Corrosion resistant large contact area
----------	--


Applicable temperature range	0 ~ 60°C
------------------------------	----------

Clamping thickness	0.1 ~ 3mm
Material	PTFE + platinum sheet
Built-in 10*30 platinum sheet (size and material can be customized)	
Features	Suitable for soft samples
Applicable temperature range	0 ~ 60°C
Clamping thickness	0.1 ~ 5mm
Material	PTFE + platinum sheet
Built-in 5*15 platinum (size can be customized, material can be customized)	
Features	Length and size can be customized
Applicable temperature range	0 ~ 60°C
Clamping thickness	0.1 ~ 5mm
Material	PTFE + copper wire
Built-in 0.5mm copper wire (size and material can be customized)	



# Graphite Disc Electrode Graphite Rod Graphite Sheet Electrode

Item Number: ELEG



## Introduction


High-quality graphite electrodes for electrochemical experiments. Complete models with acid and alkali resistance, safety, durability, and customization options.

[Learn More](#)

Features	10*10*3, can be customized
Applicable temperature range	0 ~ 60°C
Rod material	PTFE
Material	High-purity graphite>99.99%
Features	2*90, can be customized
Applicable temperature range	0 ~ 60°C
Rod material	PTFE
Material	High-purity graphite>99.99%
Features	Inner core $\phi$ 2-6
Applicable temperature range	0 ~ 60°C
Rod material	PTFE
Material	High-purity graphite>99.99%

## Metal Disk Electrode

Item Number: ELEM



### Introduction

Elevate your experiments with our Metal Disk Electrode. High-quality, acid and alkali resistant, and customizable to fit your specific needs. Discover our complete models today.

[Learn More](#)

Specification	0.5 ~ 6mm, can be customized
Applicable temperature range	0 ~ 60°C
Rod material	PTFE
Material	Any material can be customized

## Glassy Carbon Electrode

Item Number: ELEGC



### Introduction

Upgrade your experiments with our Glassy Carbon Electrode. Safe, durable, and customizable to fit your specific needs. Discover our complete models today.

[Learn More](#)

Specification	Inner diameter 2~6mm, can be customized
Applicable temperature range	0 ~ 60°C
Rod material	PTFE
Material	Imported glassy carbon > 99.99%

## High Purity Metal Sheets - Gold / Platinum / Copper / Iron Etc...

Item Number: ELEGB



### Introduction


Elevate your experiments with our high-purity sheet metal. Gold, platinum, copper, iron, and more. Perfect for electrochemistry and other fields.

[Learn More](#)

Specification	customized
Applicable temperature range	0 ~ 60°C
Purity	99.99%
Material	customized

## Sample Support Body

Item Number: ELES



### Introduction


Improve your electrochemical tests with our Sample Support Body. High-quality and reliable for accurate results. Upgrade your research today.

[Learn More](#)

Reaction area	1cm <sup>2</sup> (customizable)
Applicable sample size	circular diameter > 15mm square side length > 15mm
Applicable sample thickness	3mm ~ 5mm (can be customized)
Conductive form	gold-plated copper needle
Overall material	PTFE
Dimensions	rod length 6*80mm

## Gold Disc Electrode

Item Number: ELEGD



### Introduction

Looking for a high-quality gold disc electrode for your electrochemical experiments? Look no further than our top-of-the-line product.

[Learn More](#)

Specifications	0.5 ~ 6mm, can be customized
Applicable temperature range	0 ~ 60°C
Rod Material	PTFE
Guide material	high purity gold> 99.99%

## Platinum Disc Electrode

Item Number: ELEP



### Introduction


Upgrade your electrochemical experiments with our Platinum Disc Electrode. High-quality and reliable for accurate results.

[Learn More](#)

Specifications	0.5 ~ 6mm, can be customized
Applicable temperature range	0 ~ 60°C
Rod Material	PTFE
Guide material	high Purity Platinum> 99.99%

## Glassy Carbon Sheet - Rvc

Item Number: ELEGCS



### Introduction

Discover our Glassy Carbon Sheet - RVC. Perfect for your experiments, this high-quality material will elevate your research to the next level.


[Learn More](#)

Specifications	10*10*1mm ~ can be customized
Applicable temperature range	0 ~ 60°C
Guide sheet material	imported glass carbon



## Platinum Sheet Electrode

Item Number: ELEPS



### Introduction


Elevate your experiments with our Platinum Sheet Electrode. Crafted with quality materials, our safe and durable models can be tailored to fit your needs.

[Learn More](#)

Specification	5*5*0.1 mm, can be customized
Applicable temperature range	0 ~ 60°C
Rod Material	PTFE
Guide sheet material	high purity platinum > 99.99%

# Platinum Auxiliary Electrode

Item Number: ELPA



## Introduction

Optimize your electrochemical experiments with our Platinum Auxiliary Electrode. Our high-quality, customizable models are safe and durable. Upgrade today!

[Learn More](#)

Features	Corrosion Resistant
Applicable temperature range	0 ~ 80°C
Wire diameter	0.5 / 1mm
Material	pure platinum
Customize material (gold, silver, platinum, copper) and rod length to your needs.	


Features	Corrosion Resistant
Applicable temperature range	0 ~ 80°C
Wire diameter	0.5 / 1mm
Material	PTFE Rod + Platinum Wire
Customize material (gold, silver, platinum, copper) and rod length to your needs.	

Features	Corrosion Resistant
Applicable temperature range	0 ~ 80°C
Size	5*5~ 50*50mm
Material	PTFE Rod + Platinum Mesh
Pure platinum wire braided mesh electrode, high purity and large surface area.	

Features	Corrosion Resistant
Applicable temperature range	0 ~ 80°C
Wire diameter	1mm ~ 2mm
Material	PTFE Rod + Platinum
Customize material (gold, silver, platinum, copper) and rod length to your needs.	

## Gold Sheet Electrode

Item Number: ELEGS



### Introduction

Discover high-quality gold sheet electrodes for safe and durable electrochemical experiments. Choose from complete models or customize to meet your specific needs.

[Learn More](#)

Specifications	5*5*0.1 mm ~ can be customized
Applicable temperature range	0 ~ 60°C
Rod Material	PTFE
Guide material	high purity gold> 99.99%

# Reference Electrode Calomel / Silver Chloride / Mercury Sulfate

Item Number: ELERA



## Introduction

Find high-quality reference electrodes for electrochemical experiments with complete specifications. Our models offer resistance to acid and alkali, durability, and safety, with customization options available to meet your specific needs.

[Learn More](#)

Features	Good reproducibility, accurate potential application
----------	--

Applicable temperature range	0 ~ 25°C
------------------------------	----------

Dimensions	The overall length is 140mm, with the upper tube measuring 9.5mm by 35mm and the lower tube measuring 6mm by 65mm.
------------	--

Types	Amalgam-mercury type. It offers a neutral charge and is available in three variations: single salt bridge, double salt bridge, and bent tube.
-------	---

Features	suitable for small volumes
----------	----------------------------

Applicable temperature range	0 ~ 40°C
------------------------------	----------

Dimensions	90mm overall length, 4*45mm in the down tube
------------	--

The electrode properties are Ag/AgCl

Features	suitable for any situation
----------	----------------------------

Applicable temperature range	0 ~ 60°C
------------------------------	----------

Dimensions	105mm overall length, 6*45mm in the down tube
------------	---

The nature of the electrode is Ag/AgCl, and the curved tube can be customized for silver chloride

Features	Potential stability
----------	---------------------

Applicable temperature range	0 ~ 60°C
------------------------------	----------

Dimensions	The overall size of the unit is 140mm, with the upper tube measuring $\phi 9.5 \times 35$ mm and the lower tube measuring $\phi 6 \times 65$ mm.
------------	--

Types	Ag/AgCl type, neutral electrode; there are two kinds of single salt bridge and double salt bridge
-------	---

Features	use acidic electrolyte
----------	------------------------

Applicable temperature range	0 ~ 60°C
------------------------------	----------

Dimensions	The overall size of the unit is 140mm, with the upper tube measuring $\phi 9.5 \times 35$ mm and the lower tube measuring $\phi 6 \times 65$ mm.
------------	--

Types	Mercury type, acid electrode; there are two kinds of single salt bridge and double salt bridge
-------	--

Features	Suitable for alkaline electrolytes
----------	------------------------------------

Applicable temperature range	0 ~ 60°C
------------------------------	----------

Dimensions	The overall size of the unit is 140mm, with the upper tube measuring $\phi 9.5 \times 35$ mm and the lower tube measuring $\phi 6 \times 65$ mm.
------------	--

Types	Mercury type, alkaline electrode; there are two kinds of single salt bridge and double salt bridge
-------	--

Features	Suitable for long-term reactions
----------	----------------------------------

Applicable temperature range	0 ~ 60°C
------------------------------	----------

Dimensions	The overall size of the unit is 145mm, the lower tube measuring $\phi 9.2 \times 120$ mm. Wiring is U-shaped blade
------------	--

Types	The nature of the electrode is Ag/AgCl type, which can react unattended for a long time
-------	---

Features	Suitable for long-term reactions
----------	----------------------------------

Applicable temperature range	0 ~ 60°C
------------------------------	----------

Dimensions	The overall size of the unit is 145mm, the lower tube measuring $\phi 9.2 \times 120$ mm. Wiring is U-shaped blade
------------	--

Types	The nature of the electrode is Ag/AgCl type, and the second liquid junction of the double junction type can be added on demand
-------	--

Features	Protective electrode, easy to use
----------	-----------------------------------

Applicable temperature range	0 ~ 80°C
------------------------------	----------

Dimensions	Standard $\phi 10 \times 70$ mm, extended $\phi 10 \times 100$ mm
------------	---

Types	The built-in sand core liquid junction is used to protect the electrode and reduce the liquid junction potential
-------	--

Features	Protective electrode, easy to use
----------	-----------------------------------

Applicable temperature range	0 ~ 80°C
------------------------------	----------

Dimensions	Standard $\phi 10 \times 70$ mm, extended $\phi 10 \times 100$ mm
------------	---

Used to protect the electrode and reduce the liquid junction potential

Features	Protective electrode, easy to use
----------	-----------------------------------

Applicable temperature range	0 ~ 80°C
------------------------------	----------

Dimensions	$\phi 12 \times 70$ mm / $\phi 6 \times 70$ mm / $\phi 6 \times 100$
------------	--

Used to protect the electrode and reduce the liquid junction potential

Features	Protective electrode, easy to use
----------	-----------------------------------


Applicable temperature range	0 ~ 50°C
------------------------------	----------

Dimensions	$\phi 6 \times 80$ mm / $\phi 10 \times 80$ mm
------------	--

The guard electrode reduces the liquid junction potential

## Copper Sulfate Reference Electrode

Item Number: ELERCS



### Introduction

Looking for a Copper Sulfate Reference Electrode? Our complete models are made of high-quality materials, ensuring durability and safety. Customization options available.

[Learn More](#)

Specifications	ceramic core / cork core
Rod material	pp
Usage	Inject distilled water on top of the powder

# Flat Corrosion Electrolytic Cell

Item Number: ELEFC



## Introduction

Discover our flat corrosion electrolytic cell for electrochemical experiments. With exceptional corrosion resistance and complete specifications, our cell guarantees optimal performance. Our high-quality materials and good sealing ensure a safe and durable product, and customization options are available.

[Learn More](#)

Specifications	350ml, can be customized
Applicable temperature range	0 ~ 70°C
Sealing form	TSilicone rubber gasket
Material	boron glass + PTFE
Hole	three grinding mouths + two inner circulation pagoda mouths
Specifications	350ml, can be customized
Applicable temperature range	0 ~ 100°C
Material	boron glass + PTFE
Hole	Three grinding mouth two circulation + water bath

# Quartz Electrolytic Cell

Item Number: ELEQ



## Introduction

Looking for a reliable quartz electrochemical cell? Our product boasts excellent corrosion resistance and complete specifications. With high-quality materials and good sealing, it's both safe and durable. Customize to meet your needs.

[Learn More](#)

Specifications	10ml ~ 1000ml
Applicable temperature range	0 ~ 60°C
Sealing form	thread + apron
Material	Quartz glass + PTFE
Opening hole of electrolytic cell	Three electrode holes (6mm), Two air holes (3mm), can be customized
Specifications	10ml ~ 1000ml
Applicable temperature range	0 ~ 60°C
Material	Quartz glass + PTFE
Opening hole of electrolytic cell	Three electrode holes (6mm)



## Coating Evaluation Electrolytic Cell

Item Number: ELEC



### Introduction

Looking for corrosion-resistant coating evaluation electrolytic cells for electrochemical experiments? Our cells boast complete specifications, good sealing, high-quality materials, safety, and durability. Plus, they're easily customizable to meet your needs.

[Learn More](#)

Specifications	8/30/50/80ml
Applicable temperature range	0 ~ 60°C
Reaction area	0.5~ 2cm <sup>2</sup>
Material	boron glass + PTFE
Opening hole of electrolytic cell	Two electrode holes (including graphite rod electrode*1 silver chloride electrode*1)

## Side Window Optical Electrolytic Cell

Item Number: ELCOS



### Introduction

Experience reliable and efficient electrochemical experiments with a side window optical electrolytic cell. Boasting corrosion resistance and complete specifications, this cell is customizable and built to last.

[Learn More](#)

Specifications	50ml ~ 1000ml
Applicable temperature range	0 ~ 60°C
Sealing form	thread
Material	glass + PTFE
Opening hole of electrolytic cell	Three electrode holes (6mm), two air holes (3mm), custom openings are available
Specifications	50ml ~ 1000ml
Applicable temperature range	0 ~ 60°C
Sealing form	thread
Material	PTFE
Opening hole of electrolytic cell	Three electrode holes (6mm), two air holes (3mm), custom openings are available

## Thin-Layer Spectral Electrolysis Cell

Item Number: ELCST



### Introduction

Discover the benefits of our thin-layer spectral electrolysis cell. Corrosion-resistant, complete specifications, and customizable for your needs.

[Learn More](#)

Specifications	water system / non-water system
Applicable temperature range	room temperature
Sealing form	non-sealed
Material	Quartz + PTFE
Opening hole of electrolytic cell	three electrode holes (including platinum wire electrode, silver chloride electrode, platinum mesh electrode)

## Electrode Polishing Material

Item Number: ELMP




### Introduction

Looking for a way to polish your electrodes for electrochemical experiments? Our polishing materials are here to help! Follow our easy instructions for best results.

[Learn More](#)

# Conductive Carbon Cloth / Carbon Paper / Carbon Felt

Item Number: ELCPF



## Introduction

Conductive carbon cloth, paper, and felt for electrochemical experiments. High-quality materials for reliable and accurate results. Order now for customization options.

[Learn More](#)


Model	HCP330N (hydrophilic)	HCP330P (waterproof, that is, PTFE treatment)	HCP331N (hydrophilic)	HCP331P (waterproof, that is, PTFE treatment)
Thickness	0.29±0.02mm	0.380.02mm	0.340.02mm	0.350.02mm
Size	36*18cm	36*18cm	336*18cm	36*18cm
Unit weight	160-190 g/m <sup>2</sup>	175-205g/m <sup>2</sup>	200-230g/m <sup>2</sup>	200-230g/m <sup>2</sup>
Longitudinal resistance	< 0.12 × 10 <sup>-2</sup> Ω	< 0.35 × 10 <sup>-2</sup> Ω	< 0.11 × 10 <sup>-2</sup> Ω	< 0.2 × 10 <sup>-2</sup> Ω

Model	WIS1010	WIS1011
Thickness	0.38mm	0.41mm
Basic Weight	180g/m <sup>2</sup>	200g/m <sup>2</sup>
Air Permeability	< 55sec	< 55sec
Through.Plane Resistance	< 13 mΩcm <sup>2</sup>	< 13 mΩcm <sup>2</sup>
Tensile Strength (MD)	10 N/cm	10 N/cm
Tensile Strength (XD)	5 N/cm	5 N/cm

Density	70-600 g/m <sup>2</sup>
Thickness size	1 ~ 12 mm
Carbon content	≥90%
Specific surface area	≥1500m <sup>2</sup> /g

## Conductive Carbon Fiber Brush

Item Number: ELBCF



### Introduction


Discover the benefits of using conductive carbon fiber brush for microbial cultivation and electrochemical testing. Improve your anode's performance.

[Learn More](#)

Material	carbon fiber wire
Size	3*3*12 cm - 3*30*35 cm, Can be customized

## Foam Metal Sheet - Copper Foam / Nickel

Item Number: ELFMS



### Introduction

Discover the benefits of foam metal sheets for electrochemical tests. Our foam copper/nickel sheets are ideal for current collectors and capacitors.

[Learn More](#)



## Kintek Solution

Head Quarter: No.89 Science Avenue, High-Tech Zone,  
Zhengzhou, China

Hongkong Office: 300 Lockhart Road, Wan Chai,  
Hongkong

Canada Office: Boulevard Graham, Mont-Royal, QC, H3P  
2C7, Canada

