



KINTEK SOLUTION

Manual Heated Lab Press Catalog

Contact us for more catalogs of [Sample Preparation](#), [Thermal Equipment](#), [Lab Consumables & Materials](#), [Bio-Chem Equipment](#), etc...

KINTEK SOLUTION

COMPANY PROFILE

>>> About Us

Kintek Solution Ltd is one technology orientated organization, team members are devoted to probing the most efficient and reliable technology and innovations in the scientific researching equipment, fields like biochemical reacting, new materials researching, heat treatment, vacuum creating, refrigerating, as well as pharmaceutical and petroleum extracting equipment.

In the past 20 years, we earned rich experiences in this researching equipment field, we are capable to supply both the equipment and solution according to customer's needs and realities, we have also developed lots of customer tailored equipment according to a specific working purpose, and we have lots of successful projects in many universities and institutes from different countries, like Asia, Europe, North and South America, Australia and New Zealand, Middle East, and Africa.

Profession, quick response, hard working, and sincerity is a remarkable label of our team members working attitude, which earn us a sound reputation among our clients.

We are here and ready to service our clients from different countries and regions, and share the most efficient and reliable technology together!



Hydraulic Heated Lab Pellet Press 24T / 30T / 60T

Item Number: PCH



Introduction

Looking for a reliable Hydraulic Heated Lab Press? Our 24T / 40T model is perfect for material research labs, pharmacy, ceramics, and more. With a small footprint and the ability to work inside a vacuum glove box, it's the efficient and versatile solution for your sample preparation needs.

[Learn More](#)

Instrument model	PCH-24T1010	PCH-30T2020	PCH-60T1818
Pressure Range	0-24.0 tons	0-30.0 tons	0-60.0 tons
piston diameter	95mm (d) in chrome plated oil cylinder	110mm (d) in chrome plated oil cylinder	150mm (d) in chrome plated oil cylinder
Main overall structure	Equipment without sealed connections to reduce oil leakage points	Equipment without sealed connections to reduce oil leakage points	Equipment without sealed connections to reduce oil leakage points
Mold heating temperature	Room temperature-300.0C/500.0C	Room temperature -300.0C/500.0C	Room temperature-300.0C/500.0C
Insulation method	Imported insulation board	Imported insulation board	Imported insulation board
Cooling method	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]
Hot platen size	100×100mm (M×N)with chamfer	200×200mm(M×N)	180×180mm (M×N)
Host size	245×175×500mm(K×P×H)	405×260×525mm(K×P×H)	405 ×260×525mm(K×P×H)
Dimensions	500×175×500mm(L×W×H)	950×260×525mm(L×W×H)	950×260×525mm(L×W×H)
power supply	600 W(220V/110V can be customized)	1200 W(220V/110V can be customized)	1000 W(220V/110V can be customized)
Weight	60 Kg	180 Kg	180 Kg

Integrated Manual Heated Lab Pellet Press 120Mm / 180Mm / 200Mm / 300Mm

Item Number: PCY



Introduction

Efficiently process heat-pressing samples with our Integrated Manual Heated Lab Press. With a heating range up to 500°C, it's perfect for various industries.

[Learn More](#)

Instrument model	PCY-5T1212	PCY-10T1818	PCY-10T2020	PCY-15T3030
Pressure Range	0-5.0 tons	0-10.0 tons	0-10.0 tons	0-15.0 tons
Piston diameter	50mm (d) in chrome plated oil cylinder	65mm (d) in chrome plated oil cylinder	65mm (d) in chrome plated oil cylinder	95mm (d) in chrome plated oil cylinder
Main overall structure	Equipment without sealed connections to reduce oil leakage points	Equipment without sealed connections to reduce oil leakage points	Equipment without sealed connections to reduce oil leakage points	Equipment without sealed connections to reduce oil leakage points
Mold heating temperature	Room temperature -300.0C/500.0C	Room temperature-300.0C/500.0C	Room temperature-300.0C/500.0C	Room temperature-300.0C/500.0C
Insulation method	Imported insulation board	Imported insulation board	Imported insulation board	Imported insulation board
Cooling method	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]
Hot platen size	Double plate heating 120×120mm(M×N)	Double plate heating 180×180mm(M×N)	Double plate heating 200×200mm(M×N)	Double plate heating 300×300mm(M×N)
Workspace	140×140×60mm	180×180×60mm	200×200×60 mm	300×300×65mm
Dimensions	250×230×390mm(L×W×H)	290×290×420mm(L×W×H)	320×290×420mm(L×W×H)	450×420×450mm(L×W×H)
Power supply	700W(220V/110V can be customized)	1000 W(220V/110V can be customized)	1200 W(220V/110V can be customized)	3000 W(220V/110V can be customized)
Weight	55 Kg	90 Kg	95Kg	180Kg
Dimensional diagram of powder tablet press	See picture below	See picture below	See picture below	See picture below

Split Manual Heated Lab Pellet Press 30T / 40T

Item Number: PCSM



Introduction

Efficiently prepare your samples with our Split Manual Heated Lab Press. With a pressure range up to 40T and heating plates up to 300°C, it's perfect for various industries.

[Learn More](#)

Instrument model	PCSM-30T3030	PCSM-40T4040
Pressure Range	0-30.0 tons	0-40.0 tons
Piston diameter	130mm (d) in chrome plated oil cylinder	130mm (d) in chrome plated oil cylinder
Main overall structure	Equipment without sealed connections to reduce oil leakage points	Equipment without sealed connections to reduce oil leakage points
Mold heating temperature	Room temperature-300.0C/500.0C	Room temperature-300.0C
Insulation method	Imported insulation board	Imported insulation board
Cooling method	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]
Hot platen size	300×300mm (M×N)	400×400mm(M×N)
Host size	380×350×600mm(K×P×H)	500×480×650(K×P×H)
Dimensions	700×400×600mm(L×W×H)	800×480×650(L×W×H)
Power supply	3000 W(220V/110V can be customized)	5000 W(220V/110V can be customized)
Weight	260 Kg	460Kg
Dimensional diagram of powder tablet press	See picture below	See picture below



Kintek Solution

Head Quarter: No.89 Science Avenue, High-Tech Zone,
Zhengzhou, China

