Electric Lab Cold Isostatic Press Cip Machine For Cold Isostatic Pressing

Item Number: PCIE

Introduction

Produce dense, uniform parts with improved mechanical properties with our Electric Lab Cold Isostatic Press. Widely used in material research, pharmacy, and electronic industries. Efficient, compact, and vacuum-compatible.

Learn More

Instrument model	PCIE-12T	PCIE-20T	PCIE-40T	PCIE-60T
Pressure Range	0-12T(0-17MPa)	0-20T(0-21MPa)	0-40T(0-30MPa)	0-60T(0-34MPa)
Piston diameter	95mm (d) in chrome plated oil cylinder	110mm (d) in chrome plated oil cylinder	130mm (d) in chrome plated oil cylinder	150mm (d) in chrome plated oil cylinder
Pressure gage	Digital display0.0-40.0MPa	Digital display0.0-40.0MPa	Digital display0.0-40.0MPa	Digital display0.0-40.0MPa
Maximum piston stroke (T)	40mm	40mm	50mm	50mm
Way of Pressure	Electric pressurization/manual pressurization	Electric pressurization/manual pressurization	Electric pressurization/manual pressurization	Electric pressurization/manual pressurization
Pressure replenishment method	Automatic pressurization/manual slow pressurization	Automatic pressurization/manual slow pressurizatio	Automatic pressurization/manual slow pressurization	Automatic pressurization/manual slow pressurization
guard	Organic glass	Organic glass	Organic glass	Organic glass
ambient temperature	10℃-40℃	10℃-40℃	10℃-40℃	10℃-40℃
Isostatic pressure	0-300MPa	0-300MPa	0-300MPa	0-300MPa
Isostatic pressure chamber	Φ22×70mm(M×N)	Φ30×120mm(M×N)	Φ40×150mm(M×N)	Φ50×150mm(M×N)
External dimensions	305×430×530mm(L×W×H)	305×430×600mm(L×W×H)	355×450×710mm(L×W×H)	405×470×720mm(L×W×H)
power supply	550W(220V/110 can be customized)	550W(220V/110 can be customized)	550W(220V/110 can be customized)	550W(220V/110 can be customized)
Equipment weight	110Kg	120Kg	150Kg	200Kg