

# Herbal Powder Sterilization Autoclave Machine For Chinese Medicine

Item Number: KT-Q01



## Introduction

The herbal powder sterilization autoclave machine for Chinese medicine uses saturated steam for effective sterilization. It utilizes the heat and penetrative properties of steam, achieves sterilization after heat preservation, and maintains a good drying effect with a dedicated drying system.

[Learn More](#)

Specifications	Dimensions	Chamber size	steam consumption	Number of sterilization trays	electricity	Equipment net weight
KT-G0.25JS(F)	1100*1350*1900	800*600*600	18KG	18	2+(24)	900KG
KT-G0.36JS(F)	1300*1350*1900	1000*600*600	25KG	18	2+(24)	1000KG
KT-G0.6JS(F)	1550*1400*1900	1250*610*910	30KG	26	3+(36)	1400KG
KT-G0.8JS(F)	1750*1400*1900	1450*610*910	40KG	26	3+(36)	1600KG
KT-G1.0JS	1550*1550*1900	1250*680*1180	45KG	36	3KW	1700KG
KT-G1.2JS	1750*1500*1900	1450*680*1180	50KG	36	4KW	1800KG
KT-G1.5JS	2150*1500*1900	1850*680*1180	60KG	72	4KW	2000KG
KT-G2.0JS	1950*1500*1900	1600*900*1400	65KG	88	4.5KW	2500KG
KT-G2.5JS	2350*1500*1900	2000*900*1400	75KG	88	6KW	3000KG
KT-G3.0JS	2750*1500*1900	2400*900*1400	90KG	88	8KW	3500KG

Specifications	Dimensions	Chamber size	steam consumption	Number of sterilization trays	electricity	Equipment net weight
KT-G0.25JS(F)	1100*1350*1900	800*600*600	25KG	12	1.2+(24)	700KG
KT-G0.36JS(F)	1300*1350*1900	1000*600*600	35KG	12	1.2+(24)	800KG
KT-G0.6JS(F)	1550*1400*1900	1250*610*910	40KG	36	2.0+(36)	1200KG
KT-G0.8JS(F)	1750*1400*1900	1450*610*910	50KG	36	2.0+(36)	1400KG
KT-G1.0JS	1550*1500*1900	1250*680*1180	60KG	48	2.5KW	1550KG
KT-G1.2JS	1750*1500*1900	1450*680*1180	70KG	72	2.5KW	1650KG
KT-G1.5JS	2150*1500*1900	1850*680*1180	80KG	96	3.5KW	1800KG
KT-G2.0JS	1950*1850*2200	1600*900*1400	100KG	60	4.5KW	2200KG
KT-G2.5JS	2350*1850*2200	2000*900*1400	120KG	120	4.5KW	2600KG
KT-G3.0JS	2750*1850*2200	2000*900*1400	140KG	120	6KW	3000KG

Specifications	Dimensions	Chamber size	steam consumption	ozone depletion	Number of sterilization trays	electricity	Equipment net weight
KT-G0.25J(S)(F)	1100*1350*1900	800*600*600	25KG	4	12	2+(24)	980KG
KT-G0.36J(S)(F)	1300*1350*1900	1000*600*600	35KG	4	12	2+(24)	1080KG
KT-G0.6J(S)(F)	1550*1400*1900	1250*610*910	40KG	7	36	3+(36)	1500KG
KT-G0.8J(S)(F)	1750*1400*1900	1450*610*910	50KG	9	36	3+(36)	1700KG
KT-G1.0J(S)	1550*1500*1900	1250*680*1180	60KG	11	48	3KW	1800KG
KT-G1.2J(S)	1750*1500*1900	1450*680*1180	70KG	13	72	4KW	1900KG
KT-G1.5J(S)	2150*1500*1900	1850*680*1180	80KG	16	96	4KW	2100KG
KT-G2.0J(S)	1950*1850*2200	1600*900*1400	100KG	20	60	4.5KW	2600KG
KT-G2.5J(S)	2350*1850*2200	2000*900*1400	120KG	25	120	6KW	3100KG
KT-G3.0J(S)	2750*1850*2200	2400*900*1400	140KG	30	120	8KW	3600KG