

## **High Pressure Laboratory Vacuum Tube Furnace Quartz Tubular Furnace**

**Item Number: KT-PTF** 



## Introduction

KT-PTF High Pressure Tube Furnace: Compact split tube furnace with strong positive pressure resistance. Working temp up to 1100°C and pressure up to 15Mpa. Also works under controller atmosphere or high vacuum.

Learn More

| Furnace model  | KT-PTF                                    | KT-PTF Pro                  |  |
|--|---|-----------------------------|--|
| Temperature controller   | Digital PID controller                    | Touch screen PID controller |  |
| Multi program preset   | no  | yes                         |  |
| Power failure restarting   | no  | yes                         |  |
| Max. temperature   | 1100°C                                    |                             |  |
| Constant work temperature  | 1000°C                                    |                             |  |
| Furnace tube material  | Super nickel based alloy                  |                             |  |
| Furnace tube diameter  | 50 / 60 / 80 / 100 mm                     |                             |  |
| Heating zone length  | 300 / 450 / 600 / 800 mm                  |                             |  |
| Heating zone quantity  | 1-10 zones                                |                             |  |
| Vacuum sealing solution  | SS 304 flange with solid copper seal ring |                             |  |
| Rated vacuum pressure  | 0.001Pa/10E5 torr                         |                             |  |
| Rated positive pressure  | 15 Mpa                                    |                             |  |
| Chamber material   | Japan Al2O3 alumina fiber                 |                             |  |
| Heating element  | Cr2Al2Mo2 wire coil                       |                             |  |
| Temperature sensor   | Build in K type Thermal couple            |                             |  |
| Temperature control accuracy   | ±1°C                                      |                             |  |
| Temperature uniformity   | ±5°C                                      |                             |  |
| Electric power supply  | AC110-220V,50/60HZ                        |                             |  |
| Other super nickel based alloy tube size and heating zone length can be customized |   |                             |  |
|  |   |                             |  |



| 5 | Tube thermal block hook | 1 |
|---|-------------------------|---|
| 6 | Heat resistant glove    | 1 |
| 7 | Operation manual        | 1 |