

Horizontal Autoclave Steam Sterilizer

Item Number: KT-P01



Introduction

The horizontal autoclave steam sterilizer adopts the gravity displacement method to remove the cold air in the inner chamber, so that the inner steam and cold air content is less, and the sterilization is more reliable.

[Learn More](#)

Model	KT-150YDA	KT-200YDA	KT-280YDA	KT-400YDA	KT-500YDA
Sterilization chamber volume	150L φ440×1000	200L φ515×1000	280L φ600×1000	400L φ700×1100	500L φ700×1300mm
Fixed work stress	0.22Mpa				
Rated working temperature	134°C				
Sterilization temperature selection	40°C-134°C				
Timing time selection range	0-60min				
Heat uniformity of sterilization room	≤±2°C				
Power/supply voltage	9kw/380V 50Hz	9kw/380V 50Hz	12kw/380V 50Hz	18kw/380V 50Hz	18kw/380V 50Hz
Dimensions (mm)	1400×600×1300	1400×670×1650	1400×770×1780	1430×880×1830	1800×900×1820
Transport size (mm)	1560×750×1850	1560×820×1850	1680×920×2100	1600×1050×2100	1850×1050×2100
Gross weight/net weight	320/240kg	350/260kg	465/365Kg	530/420Kg	580/470Kg