

# Silicon Carbide (Sic) Ceramic Sheet Wear-Resistant

Item Number: KM-DG02



## Introduction

Silicon carbide (sic) ceramic sheet is composed of high-purity silicon carbide and ultra-fine powder, which is formed by vibration molding and high-temperature sintering.

[Learn More](#)

Round 15*3mm	40*40*1mm	50*50*4/5/6mm	100*100*5mm	150*150*5mm
5*5*1mm	40*40*2mm	50*50*8/10mm	100*100*7mm	15*15*1mm (one side polished)
10*10*4mm	50*50*1mm	50*50*14mm	100*100*10mm	50*50*1mm (one side polished)
20*20*3mm	50*50*2mm	100*100*3mm	100*100*15mm	
20*20*5mm	50*50*3mm	100*100*4mm	100*100*20mm	

Project	Unit	Vacuum Sintering SiC	Reaction Bonded SiC
Density	g/cc	3.12	3.05-3.08
Surface roughness	um	0.6	0.6-0.8
Hardness	Hs	115	110
Apparent porosity	%	0.2	0.3
Compressive strength	MPa	2500	2500
Flexural strength	MPa	380	350
Free silicon content	%	1	10
Purity (Silicon Carbide Content)	%	≥99	≥90
Elastic modulus	GPa	410	400
Thermal conductivity	Cal/cm.s.°C	0.3	0.32
Coefficient of thermal expansion	i/°C	4.2×10 <sup>-6</sup>	4×10 <sup>-6</sup>
Operating temperature	°C	1400	1300