

KINTEK SOLUTION

# **Engineering Ceramics Catalog**

Contact us for more catalogs of Sample Preparation, Thermal Equipment, Lab Consumables & Materials, Bio-Chem Equipment, etc...



# KINTEK SOLUTION

### COMPANY PROFILE

### >>> About Us

Kintek Solution Ltd is one technology orientated organization, team members are devoted to probing the most efficieent and reliable technology and innovations in the scienticfic researching equipment, fields like biochemical reacting, new materials researching, heat treatment, vaccum creating, refrigerating, as while as pharmaceutical and petroleum extracting equipment.

In the past 20 years, we earned rich experiences in this researing equipment field, we are capable to supply both the equipment and solution according to customer's needs and realities, we have also developed lots of customer tailer equipment accoding to a specific working purpose, and we have lots of successful projects in many universities and institutes from different countries, like Asia, Europe, North and south America, Australia and New Zealand, middle east, and Africa.

Profession, quick response, hard working, and sincerity is a remarkable label of our team meambers working attitude, which earn us a sound reputation among our clients.

We are here and ready to service our clients from different countries and regions, and share the most efficent and reliable technology together!





### **Boron Nitride (Bn) Ceramic Rod**

**Item Number: KM-D4** 



### Introduction

Boron nitride (BN) rod is the strongest boron nitride crystal form like graphite, which has excellent electrical insulation, chemical stability and dielectric properties.

Learn More

diameter and length

10-100mm\*100-300mm



### **Boron Nitride (Bn) Ceramic Tube**

**Item Number: KM-D5** 



### Introduction

Boron nitride (BN) is known for its high thermal stability, excellent electrical insulating properties and lubricating properties.



# **Hexagonal Boron Nitride (Hbn) Ceramic Ring**

**Item Number: KM-D6** 




### Introduction

Boron nitride ceramic (BN) rings are commonly used in high temperature applications such as furnace fixtures, heat exchangers and semiconductor processing.



### **Boron Nitride (Bn) Ceramic Plate**

**Item Number: KM-D7** 



### Introduction

Boron nitride (BN) ceramic plates do not use aluminum water to wet, and can provide comprehensive protection for the surface of materials that directly contact molten aluminum, magnesium, zinc alloys and their slag.



### **Boron Nitride (Bn) Ceramic Custom Parts**

**Item Number: KM-D8** 



### Introduction

Boron nitride (BN) ceramics can have different shapes, so they can be manufactured to generate high temperature, high pressure, insulation and heat dissipation to avoid neutron radiation.



# **Boron Nitride (Bn) Ceramics-Conductive Composite**

**Item Number: KM-D9** 




### Introduction

Due to the characteristics of boron nitride itself, the dielectric constant and dielectric loss are very small, so it is an ideal electrical insulating material.



### Alumina Crucibles (Al2O3) Covered Thermal Analysis / Tga / Dta

**Item Number: KM-C04** 



#### Introduction

TGA/DTA thermal analysis vessels are made of aluminum oxide (corundum or aluminum oxide). It can withstand high temperature and is suitable for analyzing materials that require high temperature testing.

Fine grinding	Alumina content: 99.5%	Alumina content is high in purity,Relatively low alumina content.	Color: pure white	High-purity alumina is slightly yellowed after firing	Fine grinding outer circle	Precise size, fine processing, no impurity particles	
Regular	Alumina content:95%	less interference to the experiment	Color: yellowish	95% alumina is pure white in color after firing	Unground outer circle	Regular for thermal analysis, not finely ground	
ф 5x2.5 regular models	ф 10x10 Regular	Φ6.5x4 fine grinding	Φ5x5 conventional	Φ5mm cover fine grinding	ф 6.8x4 regular model	Φ5.88x12.77 fine grinding	Φ6x4 fine grinding
ф 6x4.5 regular models	Φ5x3 fine grinding	ф 12x12 Regular	Φ6.5x8 fine grinding	Φ5x8 Regular	ф 6mm lid fine grinding	ф 7x4 conventional	Φ9x4 Regular
Φ9x4 fine grinding	ф 6.5x4 regular model	Φ5x4 fine grinding	ф 5mm lid regular type	ф 6.5x10 fine grinding	Φ5.3x3.5 fine grinding	ф 6.8mm lid fine grinding	
Φ5x2.5 fine grinding	Φ10x10 fine grinding	ф 6.5x8 regular model	Φ5x5 fine grinding	ф6mm cover regular type	Φ6.8x4 fine grinding	φ 6x4 conventional	
Φ6x4.5 fine grinding	Φ5x4 conventional	ф 12x12 fine grinding	ф 6.5x10 regular models	Φ5x8 fine grinding	Φ6.8mm cover regular type	Φ7x4 fine grinding	



# **Alumina Ceramic Saggar - Fine Corundum**

**Item Number: KM-C05** 



### Introduction

Alumina sagger products have the characteristics of high temperature resistance, good thermal shock stability, small expansion coefficient, anti-stripping, and good antipowdering performance.

fine striped sagger	100x100x13mm95	105x105x12mm99
fine striped sagger	103x103x22mm	118x100x19mm
fine striped sagger	120x120x40mm	195x100x32mm
Fine corundum burning table	100x100x15mm95 aluminum oxide - notched	105x105x12mm99 aluminum oxide - notched
Fine corundum burning table	250*250mm	



# Alumina (Al2O3) Furnace Tube - High Temperature

**Item Number: KM-C06** 



### Introduction

High temperature alumina furnace tube combines the advantages of high hardness of alumina, good chemical inertness and steel, and has excellent wear resistance, thermal shock resistance and mechanical shock resistance.

outer 4mm inner 2mm (1 meter)	outer 12mm inner 8nn (1 meter)	outer 25mm inner 19mm (1 meter)	outer 45mm inner 36mm (1 meter)	outer 70mm inner 60mm (1 meter)
outer 5mm inner 3mm (1 meter)	outside 16mm inside 11mm (1 meter)	outside 30mm inside 24mm (1 meter)	outside 50mm inside 40mm (1 meter)	outer 80mm inner 70mm (1 meter)
outer 6mm inner 4mm (1 meter)	outer 18mm inner 13mm (1 meter)	outer 32mm inner 26mm (1 meter)	outer 55mm inner 45mm (1 meter)	outside 90mm inside 80mm (1 meter)
outer 8mm inner 5mm (1 meter)	outside 20mm inside 15mm (1 meter)	outer 35mm inner 28mm (1 meter)	outside 60mm inside 50mm (1 meter)	90mm outside 100mm inside (1 meter)
outside 10mm inside 6mm (1 meter)	outer 22mm inner 16mm (1 meter)	outer 40mm inner 32mm (1 meter)	outer 65mm inner 55mm (1 meter)	



# **Aluminum Oxide (Al2O3) Protective Tube - High Temperature**

**Item Number: KM-C07** 



### Introduction

Alumina oxide protective tube, also known as high temperature resistant corundum tube or thermocouple protection tube, is a ceramic tube mainly made of alumina (aluminum oxide).

Φ1*Φ0.3mm (double holes)	Φ3*Φ0.7mm (double holes)	Φ2*0.4mm (four holes)			
Φ1.5*Φ0.5mm (double hole)	Φ5*Φ1.5mm (double holes)	Φ4*Φ1mm (four holes)			
Φ2*Φ0.5mm (double hole)	Φ5.5*Φ1.5mm (double holes)	Φ5*Φ1.2mm (four holes)			
Φ2.5*Φ0.7mm (double holes)	Φ8*Φ2mm (double holes)	Φ8*Φ2mm (four holes)			
Ф1*0.3mm	Φ2*0.3mm	Φ3*0.7mm	Φ4*1.5mm	Ф5.5*1.5mm	Ф8*2mm
Φ1.2*0.3mm	Φ2*0.5mm	Ф3.5*0.8mm	Φ4.5*1.2mm	Φ6*1.8mm	Φ8*2.4mm
Φ1.4*0.4mm	Φ2*0.6mm	Φ3.5*1mm	Φ5*1.2mm	Ф6.5*1.8mm	Ф10*2.7mm
Ф1.5*0.4mm	Φ2.5*0.7mm	Φ4*1.2mm	Φ5*1.5mm	Φ6.5*2mm	Φ7*2mm



# **Alumina (Al2O3) Plate-High Temperature And Wear-Resistant Insulating**

**Item Number: KM-C08** 



#### Introduction

High temperature wear-resistant insulating alumina plate has excellent insulation performance and high temperature resistance.

10x10x1mm	130x32x10mm	140x85x10mm	150x150x8mm
100x100x4mm	133x133x6mm	150x100x10mm	150x150x10mm
100x100x10mm	135x30x10mm	150x140x8mm	160x160x8mm
115x70x10mm	135x135x5mm	150x150x6mm	250x250x10mm



### **Alumina (Al2O3) Ceramic Rod-Insulated**

**Item Number: KM-C09** 



### Introduction


Insulated alumina rod is a fine ceramic material. Alumina rods have excellent electrical insulating properties, high chemical resistance and low thermal expansion.

0.4*100mm	0.9*100mm	3.2*100mm	6*100mm	13*114mm	18*86mm	40*100mm	8*300mm	24*400mm
0.5*100mm	1*100mm	3.5*100mm	7*100mm	14*114mm	18*100mm	50*100mm	10*300mm	30*400mm
0.6*100mm	2*100mm	4*100mm	8*100mm	15*100mm	20*100mm	60*100mm	12*300mm	
0.8*100mm	2*150mm	4.5*90mm	9*100mm	16*100mm	25*100mm	4*300mm	15*300mm	
0.7*100mm	2.5*100mm	4.75*100mm	10*100mm	15*100mm	30*100mm	5*300mm	16*300mm	
0.8*100mm	3*100mm	5*100mm	12*100mm	16*100mm	35*100mm	6*300mm	20*300mm	



### **Aluminium Oxide (Al2O3) Ceramic Washer - Wear-Resistant**

**Item Number: KM-C10** 



### Introduction

Alumina wear-resistant ceramic washer are used for heat dissipation, which can replace aluminum heat sinks, with high temperature resistance and high thermal conductivity.

Inner 1 outer 7 thick 1.6	4 inside, 8 outside, 4 thick	Inner 6.5 outer 15.5 thick 10	Inner 8 outer 18 thick 8.5	Inner 9.2 outer 14.5 thick 3.5	Inner 13 outer 21 thick 5
Inner 1.6 outer 6 thick 1.5	Inner 4 outer 10 thick 2/3/5	Inner 7 outer 10 thick 3	Inner 8 outer 20 thick 2.5/4	Inside 9.2 outside 14.5 thick 4	Inner 14.3 outer 21.2 thick 2
Inside 2 outside 4 thick 1	Inner 5 outer 10 thick 2.5	Inner 7 outer 14 thick 2.7	Inner 8.2 outer 25 thick 3/5	Inside 9.5 outside 18 thick 3	Inner 14 outer 42 thick 5.5
Inner 2 outer 16 thick 4.5	Inner 5 outer 10 thick 2/3	Inner 7 outer 25 thick 5	Inside 8.5 outside 16 thick 3	Inside 9 outside 31 thick 10	Inside 15.5 outside 27 thick 3.5
Inside 3 outside 6 thick 1	Inner 5 outer 17.8 thick 10	Inner 7.2 outer 15.5 thick 2.1/2.4	Inner 8.6 outer 14 thick 1/1.5	Inner 10 outer 25 thick 3/5	Inner 16 outer 23 thick 0.8
Inner 3 outer 6 thick 1.5	Inner 5.5 outer 14 thick 3/5	Inner 8 outer 12 thick 4	Inner 8.6 outer 14 thick 2/3/4	Inside 10 outside 27 thick 0.6	Inner 16 outer 23 thick 2.5/4
Inner 3 outer 6 thick 2/3/5	Inside 5.5 outside 14 thick 3/10	Inner 8.1 outer 13 thick 3	Inner 8.6 outer 14 thick 5	Inside 10 outside 36.5 thick 5	Inner 16 outer 23 thick 5/7.7
Inner 3 outer 10 thick 1.5/2/3/5	Inner 6 outer 12 thick 2	Inner 8 outer 13 thick 4	Inside 9 outside 31 thick 5	Inner 10 outer 50 thick 5	Inner 16.5 outer 37 thick 5/10
Inner 3.2 outer 7.8 thick 3.8	Inner 6 outer 12 thick 3/4/5	Inner 8 outer 15 thick 1	Inner 9.2 outer 14.5 thick 2	Inner 10.5 outer 18 thick 2	Inner 17 outer 40 thick 3.5
Inner 4 outer 6 thick 1	Inside 6.5 outside 10 thick 4	Inner 8 outer 17 thick 8.5	Inner 9.2 outer 14.5 thick 2.5	Inner 12.5 outer 25.5 thick 3	Inner 23 outer 39 thick 3.5/5/10
Inner 4 outer 7 thick 2.5	Inner 6.5 outer 14 thick 2/4	Inner 8 outer 18 thick 2	Inner 9.2 outer 14.5 thick 3	Inner 12.5 outer 25.5 thick 5	Inner 31 outer 50.5 thick 3.5



# **Alumina Ceramic Screw - High Quality Insulation And High Temperature Resistance**

Item Number: KM-C011



#### Introduction

Alumina ceramic screws are fastening components made of 99.5% alumina, ideal for extreme applications requiring excellent thermal resistance, electrical insulation and chemical resistance.

M16	External hexagon	100*9.2*24.2	7.*9.2*24.2	40*9.2*24.2	
M14	External hexagon	80*10*22	50*7.6*21.9	40*9.9*21	
M12	External hexagon	75*8.1*18.8	50*10.3*18.3	25*10.3*18.4	15*10*21.2
	Inner hexagon	50*10.5*17.2	35/25*10.4*17.1	15*12.2*18.1	14*12.2*18
M10	External hexagon	70*7*16.8	35*6.6*16.6		
	Inner hexagon	50*9*14.8	35*9.1*14.8		
М8	Inner hexagon	70*5.6*14	50*4.5*11.7	35*5.3*12.9	25*5.3*12.9
	Inner hexagon	50*7.6*12.3	35*7.9*12.3		
	Flat head inner hexagon	30*-*13.8			
	"+"Type	20*-*14.2			
М6	External hexagon	55*5.2*9.7	40*4.3*9.6		
	Inner hexagon	40*5.8*9.8	25*5.9*10	15*5.9*10	
	"+"Type	40*-*12			
	Outer hexagon "" type	25*3.9*9.8			
	Round head ""type with hole	20*4.8*10			
	Inner hexagon	15*-*9.8			
M5	External hexagon	25*3.5*8	20/15*3.6*8	10/12*3.6*7.6	5*3.6*8
	Inner hexagon	35*4.7*7.8	25/20*4.9*8.1	15/12*4.9*8.1	10/5*4.9*8.1
	Round head "+"type with hole	25*-*8.6	20*-*8.5	12*-*8.5	
	Round head Inner hexagon	25*2.*9.3	12*2.8*8.6		
	Round head "" type	10*3.4*7.9			
	"+"Type	10*-*8.9			
	Round head "" type with hole	6/15*3*10			
M4	External hexagon	20*3.2*6.8	15*3.3*6.8	10*3.2*6.8	
	Inner hexagon	25*4*7	20*4.1*6.9	15*4.1*6.8	10*3.2*6.8



	Inner hexagon	25*-*8.5			
	"+" Type	12*-*8.4			
	Round head "" type	8*2.9*7	5*2.1*9.3		
	Round head "+"type with hole	3*4.5*8.9			
M3.5	"+" Type	9*-*5.3			
МЗ	External hexagon	10*3*5.5	30*3*5.4		
	Inner hexagon	30*3*5.4	20/25*3*5.4	15/10*3*5.4	8*3*5.4
	"+" Type	15*-*5.2	6*-*5.6		
	Round head "+"type	6.5*2.7*5.5			
M2.5	"+" Type	9*-*4.5	6*-*3.9		
M2	Flat head "" type half teeth	22*1.4*3.8			
	Inner hexagon	14*1.9*3.8			
	Flat head "" type	10*1.4*3.8			
	"+"thread	8*1.6*3.5			
	Round head "+" type	8*1.5*3.5			
	External hexagon	6*1.6*3.8			
	"+" Type	6*-*4.2			



# Alumina (Al<sub>2</sub>O<sub>3</sub>) Ceramic Positioning Pin - Straight Bevel

**Item Number: KM-C012** 



### Introduction

Alumina ceramic positioning pin has the characteristics of high hardness, wear resistance and high temperature resistance.

model	small head diameter	middle diameter	Bevel Diameter	length
M4	3.1mm	4.8mm	9.7mm	22mm
M5	4mm	5.5mm	9.6mm	22mm
M6	4.7mm	6.7mm	9.5mm	26mm
M8	6.3mm	8.5mm	12mm	26mm
M9	6.3mm	9.7mm	12.9mm	28.9mm
M10	8.3mm	10.7mm	13.6mm	24.5mm
M12	9.5mm	12.7mm	14.8mm	26.5mm
M13	10mm	13.7mm	16.8mm	32.9mm
model	small head diameter	middle diameter	Bevel Diameter	length
M4	3mm	4.7mm	7.7mm	24.3mm
M5	4mm	5.5mm	9.6mm	22mm
M6	4.8mm	6.7mm	9.9mm	26mm
M8	6.2mm	8.8mm	11.9mm	25.7mm
M10	8.3mm	10.6mm	14.2mm	26.7mm
M12	9.1mm	12.6mm	14.7mm	30.5mm
M14	12.5mm	14.8mm	15.7mm	28.7mm



### **Aluminum Oxide (Al2O3) Ceramics Heat Sink - Insulation**

**Item Number: KM-C013** 



### Introduction


The hole structure of the ceramic heat sink increases the heat dissipation area in contact with the air, which greatly enhances the heat dissipation effect, and the heat dissipation effect is better than that of super copper and aluminum.

1.7*3mm	10*4mm	16*1mm	20*20mm	29.5*1mm	60*1mm	100*8mm
3*3mm	10*5mm	16*4mm	20.5*1mm	30.5*1mm	57.8*6mm	107*3mm
4*2.3mm	10.5*2mm	16*5mm	22*1mm	32*5mm	70*1mm	150*5mm
6*6mm	10.5*10.5mm	17*1mm	23.5*2.5mm	35*1mm	74*1mm	200*5mm
7*3.3mm	12*1mm	18*0.63mm	25*0.5mm	40*1mm	80*1mm	
8*5mm	12*5mm	19*0.8mm	26*4mm	45*0.5mm	90*1mm	
9.5*1.3mm	14*1mm	20*1mm	26*5mm	51*1mm	100*1mm	
10*1mm	16*0.5mm	20*10mm	28*6.5mm	50*5mm	100*2mm	



# **Alumina Zirconia Special-Shaped Parts Processing Custom-Made Ceramic Plates**

Item Number: KM-C014



#### Introduction

Alumina ceramics have good electrical conductivity, mechanical strength and high temperature resistance, while zirconia ceramics are known for their high strength and high toughness and are widely used.



### **Boron Nitride (Bn) Ceramic Parts**

**Item Number: KM-P01** 



### Introduction

Boron nitride ((BN) is a compound with high melting point, high hardness, high thermal conductivity and high electrical resistivity. Its crystal structure is similar to graphene and harder than diamond.



### **Zirconia Ceramic Plate - Yttria Stabilized Precision Machined**

**Item Number: KM-G02** 



### Introduction

Yttrium-stabilized zirconia has the characteristics of high hardness and high temperature resistance, and has become an important material in the field of refractories and special ceramics.



# **Zirconia Ceramic Rod - Stabilized Yttrium Precision Machining**

Item Number: KM-G01



### Introduction

Zirconia ceramic rods are prepared by isostatic pressing, and a uniform, dense and smooth ceramic layer and transition layer are formed at high temperature and high speed.

0.2*100mm	0.7*100mm	1.2*100mm	2.5*100mm	8*100mm	15*115mm
0.3*100mm	0.8*100mm	1.5*100mm	3*100mm	10*100mm	16*115mm
0.4*100mm	0.9*100mm	1.6*100mm	4*100mm	12*100mm	18*115mm
0.5*100mm	1*100mm	1.8*100mm	5*100mm	13*115mm	20*115mm
0.6*100mm	1.1*100mm	2*100mm	6*100mm	14*115mm	22*200mm



# **Zirconia Ceramic Ball - Precision Machining**

Item Number: KM-G03



### Introduction

zirconia ceramic ball have the characteristics of high strength, high hardness, PPM wear level, high fracture toughness, good wear resistance, and high specific gravity.

1mm	2.778mm	4.763mm	6.747mm	9.0mm	12.7mm	16.668mm	25.0mm	40mm
1.2mm	3.0mm	5.0mm	7.0mm	9.525mm	13.494mm	17.4625mm	25.4mm	50mm
1.5mm	3.175mm	5.556mm	7.144mm	10.0mm	14mm	18.256mm	28mm	
1.588mm	3.5mm	5.953mm	7.938mm	10.318mm	14.288mm	19.05mm	28.575mm	
2.0mm	3.969mm	6.0mm	8.0mm	11.1125mm	15.0mm	20.0mm	30.0mm	
2.381mm	4.0mm	6.35mm	8.5mm	11.509mm	15.875mm	20.638mm	35mm	
2.5mm	4.5mm	6.5mm	8.731mm	12.0mm	16.0mm	22.225mm	38.1mm	



## **Zirconia Ceramic Gasket - Insulating**

**Item Number: KM-G04** 



### Introduction


Zirconia insulating ceramic gasket has high melting point, high resistivity, low thermal expansion coefficient and other properties, making it an important high temperature resistant material, ceramic insulating material and ceramic sunscreen material.

5*5	13*97	148*100	22*43	Disc Diameter:
40*40	43*43	60*60	77*77	19/20/21
52*52	50*80	120*100	120*120	25/26/32
10*10	110*110	150*150	100*100	65/70/38
101*101	140*70	20*20	25*50	115/160
130*130	15*10	70*60	80*75	
42*42	56*56	50*50	125*125	
55*55	112*112	158*80	196*168	



### Silicon Carbide (Sic) Ceramic Sheet Flat / Corrugated Heat Sink

Item Number: KM-DT01



#### Introduction

Silicon carbide (sic) ceramic heat sink not only does not generate electromagnetic waves, but also can isolate electromagnetic waves and absorb part of electromagnetic waves.

25*25*3mm	30*30*5mm	40*404mm	50*50*5mm
25*25*5mm	30*30*5mm	40*40*5mm	60*60*5mm
25*25*5mm	30*30*8mm	40*40*5mm	60*60*8mm
25*25*8mm	30*30*10mm	40*40*7mm	
25*25*10mm	35*35*10mm	40*40*8mm	
30*30*2.5mm	40*40*3mm	50*50*5mm	



# Silicon Carbide (Sic) Ceramic Sheet Wear-Rresistant

**Item Number: KM-DG02** 



### Introduction


Silicon carbide (sic) ceramic sheet is composed of high-purity silicon carbide and ultra-fine powder, which is formed by vibration molding and high-temperature sintering.

Round 15*3mm	40*40*1mm	50*50*4/5/6mm	100*100*5mm	150*150*5mm
5*5*1mm	40*40*2mm	50*50*8/10mm	100*100*7mm	15*15*1mm (one side polished)
10*10*4mm	50*50*1mm	50*50*14mm	100*100*10mm	50*50*1mm (one side polished)
20*20*3mm	50*50*2mm	100*100*3mm	100*100*15mm	
20*20*5mm	50*50*3mm	100*100*4mm	100*100*20mm	



# Silicon Carbide (Sic) Ceramic Plate

**Item Number: KM-DG03** 



### Introduction


Silicon nitride (sic) ceramic is an inorganic material ceramic that does not shrink during sintering. It is a high-strength, low-density, hightemperature-resistant covalent bond compound.

25*50*5/6mm	50*50*4/5mm	100*100*4mm	100*100*12mm	150*150*6mm
25*50*10/8mm	50*50*6/8mm	100*100*5mm	100*100*15mm	150*150*8mm
50*50*1mm	50*50*10mm	100*100*6mm	100*100*16mm	150*150*10mm
50*50*2mm	100*100*2mm	100*100*8mm	100*100*30mm	
50*50*3mm	100*100*3mm	100*100*10mm	150*150*5mm	



# Silicon Nitride (Sic) Ceramic Sheet Precision Machining Ceramic

**Item Number: KM-DG04** 



#### Introduction

Silicon nitride plate is a commonly used ceramic material in the metallurgical industry due to its uniform performance at high temperatures.

Learn More

114\*114\*0.75mm 10\*10\*0.35mm 20\*20\*0.35mm 140\*190\*0.32mm 114\*114\*0.35mm



### **Aluminum Nitride (Aln) Ceramic Sheet**

**Item Number: KM-DG05** 



### Introduction

Aluminum nitride (AIN) has the characteristics of good compatibility with silicon. It is not only used as a sintering aid or reinforcing phase for structural ceramics, but its performance far exceeds that of alumina.

Product number	Product regular size (mm)	
	14*19*1	14*19*1
	20*25*1	20*25*1
Porous aluminum nitride ceramic sheet	22*28*1	22*28*1
	29*42*1	17*22*0.6
	Round140.385	
	6*30*1	114*114*1
	20*25*1	127*127*1
	3.6*3.6*0.385	139*190.5*1
	10*10*1	152.4*152.4*0.6
	30*30*1	152.4*152.4*1
	40*40*1	165*165*1
	50*50*1	25*98*0.635
Non assessed all residence with independent	1016*101.60.38	50*50*0.5
Non-porous aluminum nitride ceramic sheet	101.6*101.6*0.635	Round31*1.2
	114*114*0.385	Round26*1
	1143*114.30.635	Round72.6*0.6
	Round15*1.5	Round45*1
	Round26*1	Round45*1.5
	Round30*1	Round50*1
	Round35*1	Round50*2
	Round40*1	Round60*1





### **Kintek Solution**

Head Quarter: No.89 Science Avenue, High-Tech Zone,

Zhengzhou, China

Hongkong Office: 300 Lockhart Road, Wan Chai,

Hongkong

Canada Offce: Boulevard Graham, Mont-Royal, QC, H3P

2C7, Canada

