



KINTEK SOLUTION

Lab Hydraulic Press Catalog

Contact us for more catalogs of [Sample Preparation](#), [Thermal Equipment](#), [Lab Consumables & Materials](#), [Bio-Chem Equipment](#), etc...

KINTEK SOLUTION

COMPANY PROFILE

>>> About Us

Kintek Solution Ltd is one technology orientated organization, team members are devoted to probing the most efficient and reliable technology and innovations in the scientific researching equipment, fields like biochemical reacting, new materials researching, heat treatment, vacuum creating, refrigerating, as well as pharmaceutical and petroleum extracting equipment.

In the past 20 years, we earned rich experiences in this researching equipment field, we are capable to supply both the equipment and solution according to customer's needs and realities, we have also developed lots of customer tailored equipment according to a specific working purpose, and we have lots of successful projects in many universities and institutes from different countries, like Asia, Europe, North and South America, Australia and New Zealand, Middle East, and Africa.

Profession, quick response, hard working, and sincerity is a remarkable label of our team members working attitude, which earn us a sound reputation among our clients.

We are here and ready to service our clients from different countries and regions, and share the most efficient and reliable technology together!



Manual Lab Hydraulic Pellet Press 12T / 15T / 24T / 30T / 40T

Item Number: PCMP

Introduction

Efficient sample preparation with small footprint Manual Lab Hydraulic Press. Ideal for material researching labs, pharmacy, catalytic reaction, and ceramics.

[Learn More](#)



Instrument model	PCMP-2T	PCMP-5T	PCMP-12T
Pressure range	0-2T (25MPa)	0-5T(0-31.4MPa)	0-12T(0-30MPa)
Piston diameter	Φ32mm (d)	Φ45mm (d)	Φ70mm (d)
Integral structure	No sealing connection, oil leakage reduced	No sealing connection, oil leakage reduced	No sealing connection, oil leakage reduced
Pressure gauge	Pressure and pressure intensity display	Pressure and pressure intensity display	Pressure and pressure intensity display
Maximum pressure (T)	30mm	30mm	30mm
Pressure stability	≤1MPa/10min	≤1MPa/10min	≤1MPa/10min
Workbench diameter	Φ50mm (D)	Φ80mm (D)	Φ80mm (D)
Number of columns	Two	Two	Two
Working space	85×120mm(M×N)	96×130mm(M×N)	96×130mm(M×N)
Dimensions	210×150×350mm(L×W×H)	225×155×380mm(L×W×H)	225×155×380mm(L×W×H)
Weight	12 Kg	28Kg	28Kg

Electric Hydraulic Pellet Press For Xrf & Kbr 20T / 30T / 40T / 60T

Item Number: PCPE



Introduction

Efficiently prepare samples with the Electric Hydraulic Press. Compact and portable, it's perfect for labs and can work in a vacuum environment.

[Learn More](#)

Instrument model	PCPE-20T	PCPE-30T	PCPE-40T	PCPE-60T
Pressure range	0-20T(0-28MPa)	0-30T(0-31.5MPa)	0-40T(0-30MPa)	0-60T(0-33MPa)
Piston diameter	Φ95mm (d)	Φ110mm (d)	Φ130mm (d)	Φ150mm (d)
Integral structure	No sealing connection, oil leakage reduced	No sealing connection, oil leakage reduced	No sealing connection, oil leakage reduced	No sealing connection, oil leakage reduced
Pressure gauge	Digital display 0.00-40.00 MPa	Digital display 0.00-40.00 MPa	Digital display 0.00-40.00 MPa	Digital display 0.00-40.00 MPa
Maximum pressure (T)	30mm	40mm	50mm	50mm
Pressure stability	≤1MPa/10min	≤1MPa/10min	≤1MPa/10min	≤1MPa/10min
Pressurization mode	Electric / manual	Electric / manual	Electric / manual	Electric / manual
Compensation mode	Auto/ manual	Auto/ manual	Auto/ manual	Auto/ manual
Workbench diameter	Φ105mm (D)	Φ120mm (D)	Φ140mm(D)	Φ160mm (D)
Number of columns	Four	Four	Four	Four
Working space	80×150mm(M×N)	92×160mm(M×N)	115×185mm(M×N)	185×250mm(M×N)
Dimensions	245×415×415mm(L×W×H)	275×430×420mm(L×W×H)	295×450×500mm(L×W×H)	405×470×565mm(L×W×H)
Power supply	220V(50Hz/60Hz)	220V(50Hz/60Hz)	220V(50Hz/60Hz)	220V(50Hz/60Hz)
Weight	58Kg	72Kg	92Kg	140Kg

Force	Pressure
1 [Tons]	1.41 [MPa]
2 [Tons]	2.82 [MPa]
3 [Tons]	4.23 [MPa]
5 [Tons]	7.06 [MPa]
8 [Tons]	11.3 [MPa]
10 [Tons]	14.1 [MPa]
12 [Tons]	17 [MPa]
15 [Tons]	22.6 [MPa]

20 [Tons]

28 [MPa]

Note: The system pressure intensity shouldn't exceed 35 MPa, or else it will shorten the service life of the equipment.

Hydraulic Heated Lab Pellet Press 24T / 30T / 60T

Item Number: PCH



Introduction

Looking for a reliable Hydraulic Heated Lab Press? Our 24T / 40T model is perfect for material research labs, pharmacy, ceramics, and more. With a small footprint and the ability to work inside a vacuum glove box, it's the efficient and versatile solution for your sample preparation needs.

[Learn More](#)

Instrument model	PCH-24T1010	PCH-30T2020	PCH-60T1818
Pressure Range	0-24.0 tons	0-30.0 tons	0-60.0 tons
piston diameter	95mm (d) in chrome plated oil cylinder	110mm (d) in chrome plated oil cylinder	150mm (d) in chrome plated oil cylinder
Main overall structure	Equipment without sealed connections to reduce oil leakage points	Equipment without sealed connections to reduce oil leakage points	Equipment without sealed connections to reduce oil leakage points
Mold heating temperature	Room temperature-300.0C/500.0C	Room temperature -300.0C/500.0C	Room temperature-300.0C/500.0C
holding time	1 second to 0 seconds	1 second to 0 seconds	1 second to 0 seconds
precision	0.1°C	0.1°C	0.1°C
Insulation method	Imported insulation board	Imported insulation board	Imported insulation board
Cooling method	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]
Hot platen size	100×100mm (M×N)with chamfer	200×200mm(M×N)	180×180mm (M×N)
Host size	245×175×500mm(K×P×H)	405×260×525mm(K×P×H)	405 ×260×525mm(K×P×H)
Dimensions	500×175×500mm(L×W×H)	950×260×525mm(L×W×H)	950×260×525mm(L×W×H)
power supply	600 W(220V/110V can be customized)	1200 W(220V/110V can be customized)	1000 W(220V/110V can be customized)
Weight	60 Kg	180 Kg	180 Kg

Button Battery Press 5T

Item Number: PCBP



Introduction

Efficiently prepare samples with our 5T Button Battery Press. Ideal for material research labs and small-scale production. Small footprint, lightweight, and vacuum-compatible.

[Learn More](#)

Instrument model	PCBP-2T (Manual)	Instrument model	PCBP-1.5T(Automatic)
Pressure range	0-2T (0-25MPa)	Pressure Range	50-1500kg
Piston diameter	Φ32mm (d)	Pressurization process	Program pressurization-program pressure-timed pressure relief
Integral structure	No sealing connection, oil leakage reduced	Pressure retention time	0-999 seconds
Pressure gauge	Pressure and pressure intensity display	Pressure conversion	The program automatically converts the mold to withstand pressure
Standard die	CR20 series packaging die	LCD display	4.3-inch LCD screen
Sealing die	CR16,CR20,CR24,CR30optional	Sealing mold	Optional CR16,CR20,CR24,CR30,etc
Sealing pressure	0.8-1.2Ton	Shell removal mold	Optional CR16,CR20,CR24,CR30,etc
Disassembly die	CR16,CR20,CR24 optional	Standard mold	Standard CR20 series packaging mold
Disassembly pressure		External dimensions	220x240x380(LXWXH)
Dimensions	210×165×290mm(L×W×H)	Equipment power supply	220V(50Hz/60Hz)
Weight	12Kg	Equipment weight	35kg

Manual Lab Hydraulic Pellet Press With Safety Cover 15T / 24T / 30T / 40T / 60T

Item Number: PCF



Introduction

Efficient Manure Lab Hydraulic Press with Safety Cover for sample preparation in material research, pharmacy, and electronic industries. Available in 15T to 60T.

[Learn More](#)

Instrument model	PCF-15T
Pressure range	0-15T(0-30MPa)
Piston diameter	Φ80mm (d)
Pressure gauge	Pressure and pressure intensity display
Maximum pressure (T)	30mm
Protective cover	Plexiglass
Pressure stability	≤1MPa/10min
Workbench diameter	Φ90mm (D)
Number of columns	Four
Working space	80×130mm(M×N)
Dimensions	260×175×395mm(L×W×H)
Weight	42Kg
Force	Pressure
1[Tons]	0.75[MPa]
3[Tons]	2.2[MPa]
5 [Tons]	3.7[MPa]
10[Tons]	7.5[Mpa]

12[Tons]	9[MPa]
15[Tons]	11.3[MPa]
20[Tons]	15[MPa]
30[Tons]	22.5[MPa]
40[Tons]	30[MPa]

Note: The system pressure intensity shouldn't exceed 35 MPa, or else it will shorten the service life of the equipment.

Lab Pellet Press For Vacuum Box

Item Number: PCV



Introduction

Enhance your lab's precision with our lab press for vacuum box. Press pills and powders with ease and precision in a vacuum environment, reducing oxidation and improving consistency. Compact and easy to use with a digital pressure gauge.

[Learn More](#)

Instrument model	PCV-10T1818	PCV-10T2020
Pressure Range	0-10.0 tons	0-10.0 tons
Pressurization process	Manual pressurization	Manual pressurization
Holding time	1 second~0 seconds	1 second~0 seconds
Heating temperature	Maximum 500°C	Maximum 500°C
Heating plate	180×180mm	200×200mm
Vacuum box material	SUS 304 (stainless steel)	SUS 304 (stainless steel)
Studio Size	400×400×400mm	400×100×400mm
Door size	300×350mm	300×350mm
Vacuum degree	-0.1MPa	-0.1MPa
Dimensions	450×550×850(L×W×H)	450×550×850(L×W×H)
Power supply	220V50Hz (can support 110V)	220V50Hz (can support 110V)

Lab Pellet Press Machine For Glove Box

Item Number: PCG



Introduction

Controlled environment lab press machine for glove box. Specialized equipment for material pressing and shaping with high precision digital pressure gauge.

[Learn More](#)

Instrument model	PCG-25T1818	PCG-25T2020
Pressure Range	0-25T	0-25T
Pressurization process	Program pressurization-program pressure-timed pressure relief	Program pressurization-program pressure-timed pressure relief
Pressure retention time	0-999.59(point.Seconds)	0-999.59(point.Seconds)
Heating temperature	Up to 500°C	Up to 500°C
Heating plate	180×180mm	200×200mm
Glove box handle	St's 304	St's 304
Studio size	780×650×700	780×650×700
Transition cabin size	Φ240×260mm	Φ240×260mm
Vacuum degree	-0.1MPa	-0.1MPa
Size of the whole machine	1200×950×1800(L×W×H)	1200×950×1800(L×W×H)
Power supply	220V 50Hz	220V 50Hz

Split Electric Laboratory Pellet Press 40T / 65T / 100T / 150T / 200T

Item Number: PCES



Introduction

Efficiently prepare samples with a split electric lab press - available in various sizes and ideal for material research, pharmacy, and ceramics. Enjoy greater versatility and higher pressure with this portable and programmable option.

[Learn More](#)

Instrument model	PCES-40T	PCES-65T	PCES-100T	PCES-150T	PCES-200T
Pressure Range	0-40 tons	0-65tons	1-100tons	1-150tons	1-200tons
Piston diameter	130mm (d)	160mm (d)	200mm (d)	250mm (d)	290mm (d)
Pressurization process	Program pressurization	Program pressurization	Program pressurization	Program pressurization	Program pressurization
Hold time	1 second~ ∞ seconds	1 second ~ ∞ seconds	1second~ ∞ seconds	1second~∞ seconds	1 second~∞ seconds
Pressure conversion	Automatically converted pressure	Automatically converted pressure	Automatically converted pressure	Automatically converted pressure	Automatically converted pressure
Display	7-inch LCD	7-inch LCD	7-inch LCD	7-inch LCD	7-inch LCD
Equipment protection	Steel plate protection with organic glass door	Steel plate protection with organic glass door	Steel plate protection with organic glass door	Steel plate protection with organic glass door	Steel plate protection with organic glass door
Cylinder stroke (T)	50mm	50mm	50mm	50mm	50mm
Space size	160×300mm(M×N)	220×300mm(M×N)	260×250mm(M×N)	285×290mm(M×N)	290×300mm(M×N)
External dimensions	500×700×800mm(L×W×H)	580×700×800mm(L×W×H)	850×500×950mm(L×W×H)	950×600×1000mm(L×W×H)	1000×650×1050mm(L×W×H)
Power supply	1500W(220V/110V)	1500W(220V/110V)	1500W(220V/110V)	1500W(220V/110V)	1500W(220V/110V)
Weight	200kg	280kg	520kg	620kg	850kg

Automatic Lab Pellet Press Machine 20T / 30T / 40T / 60T / 100T

Item Number: PCEA



Introduction

Experience efficient sample preparation with our Automatic Lab Press Machine. Ideal for material research, pharmacy, ceramics, and more. Features a compact size and hydraulic press functionality with heating plates. Available in various sizes.

[Learn More](#)

Instrument model	PCEA-12T	PCEA-20T	PCEA-30T	PCEA-40T	PCEA-60T	PCEA-100T
Pressure Range	0.2-12.0 tons	1-20.0 tons	1-30.0 tons	1-40.0 tons	1-60.0 tons	1-100.0 tons
Hold time	1 second to 0 seconds	1 second to 0 seconds	1 second to 0 seconds	1 second to 0 seconds	1 second to 0 seconds	1 second to 0 seconds
Pressure conversion	Program automatically converts the pressure borne by the mold	Program automatically converts the pressure borne by the mold.	Program automatically converts the pressure borne by the mold	Program automatically converts the pressure borne by the mold	Program automatically converts the pressure borne by the mold	Program automatically converts the pressure borne by the mold
Display	4.3 inch LCD screen	4.3 inch LCD screen	4.3 inch LCD screen	4.3 inch LCD screen	7 inch LCD screen	7 inch LCD screen
Metal buttons	Silver plated contacts with a service life of over 100000	Silver plated contacts with a service life of over 100000 times	Silver plated contacts with a service life of over 100000 times	Silver plated contacts with a service life of over 100000 times	Silver plated contacts with a service life of over 100000 times	Silver plated contacts with a service life of over 100000 times
Equipment protection	Steel plate protection with organic glass door	Steel plate protection with organic glass door	Steel plate protection with organic glass door	Steel plate protection with organic glass door	Steel plate protection with organic glass door	Steel plate protection with organic glass door
Limit switch	Automatic pressure relief when the oil cylinder reaches the limit height	Automatic pressure relief when the oil cylinder reaches the limit height.	Automatic pressure relief when the oil cylinder reaches the limit height	Automatic pressure relief when the oil cylinder reaches the limit height	Automatic pressure relief when the oil cylinder reaches the limit height	Automatic pressure relief when the oil cylinder reaches the limit height
Cylinder stroke (T)	30mm	30mm	30mm	50mm	50mm	50mm
Space size	110×140mm (M×N)	140×160 mm (M×N)	140×160 mm(M×N)	175×180mm(M×N)	185×220mm(M×N)	185×250mm(M×N)
External dimensions	185×320×360 mm (L×W×H)	230×390×420mm(L×W×H)	230×390×420mm(L×W×H)	280×460×550mm(L×W×H)	300×520×580mm(L×W×H)	330×580×620mm(L×W×H)
Equipment power supply	240W(220V/110 can be customized)	550W(220V/110 can be customized)	550W(220V/110 can be customized)	550W (220V/110 can be customized)	550W(220V/110 can be customized)	1500W(220V/110 can be customized)
Equipment weight	50 Kg	90Kg	90Kg	150Kg	180Kg	240Kg

Kbr Pellet Press 2T

Item Number: PCKBR



Introduction

Introducing the KINTEK KBR Press - a handheld laboratory hydraulic press designed for entry-level users.

[Learn More](#)

Model	PCKBR-2T
Working pressure(T)	0-2(30Mpa)
Piston diameter	≤1MPa/10min
Workbench diameter	Φ45mm(D)
Number of columns	Two
Working space	54×55 (M×N)
Dimensions	100×220×220(W×L×H)
Weight(kg)	4.8kg

Manual Lab Pellet Press For Vacuum Box

Item Number: PCVM



Introduction

The lab press for vacuum box is a specialized piece of equipment designed for laboratory use. Its main purpose is to press pills and powders according to specific requirements.

[Learn More](#)

Instrument model	PCVM-10T
Pressure Range	0-10.0 tons
Pressurization process	Manual pressurization
Holding time	1 second~0 seconds
Heating temperature	Maximum 500°C
Heating plate	180x180mm□200x200mm
Vacuum box material	SUS 304 (stainless steel)
Studio Size	400x400x400mm
Door size	300x350mm
Vacuum degree	-0.1MPa
Dimensions	450x550x850(LxWxH)
powersupply	220V50Hz (can support 110V)



Kintek Solution

Head Quarter: No.89 Science Avenue, High-Tech Zone,
Zhengzhou, China

Hongkong Office: 300 Lockhart Road, Wan Chai,
Hongkong

Canada Office: Boulevard Graham, Mont-Royal, QC, H3P
2C7, Canada

