



KINTEK SOLUTION

Lab Press Catalog

Contact us for more catalogs of **Sample Preparation, Thermal Equipment, Lab Consumables & Materials, Bio-Chem Equipment, etc.**

KINTEK SOLUTION

COMPANY PROFILE

>>> About Us

Company Profile

Kintek Solution Ltd is one technology orientated organization, team members are devoted to probing the most efficient and reliable technology and innovations in the scientific researching equipment, fields like biochemical reacting, new materials researching, heat treatment, vacuum creating, refrigerating, as well as pharmaceutical and petroleum extracting equipment.

Products & Services

Kintek Solution Ltd is headquartered in Zhengzhou, the capital city of Henan Province, China, and its core business includes the manufacture, distribution and sale of all types of scientific research equipment and laboratory consumables. The wide range of products and services covers the following main areas:

- **Sample Preparation Equipment:** We provide high-performance sample preparation equipment such as tablet presses, ball mills, vibrating sieves and tablet punching machines, which are capable of meeting a wide range of sample preparation needs and ensuring high quality experimental data and research results.
- **Thermal Equipment:** Our thermal equipment includes tube furnaces, sintering furnaces, vacuum furnaces, atmosphere furnaces, graphite furnaces, dental furnaces, rotary furnaces, and high-temperature furnaces (e.g., MPCVD, CVD, PECVD, electric rotary kilns). These facilities excel in high-temperature processing and materials synthesis, meeting a wide range of needs from basic research to industrial production.
- **Biochemical equipment:** We offer a wide range of biochemical laboratory equipment, including rotary evaporators, vacuum pumps, cold trap chillers,

heating circulators, reactors, short-range distillation equipment, sterilization equipment, and homogenizers. These equipments are widely used in the fields of chemical reaction, biological processing and pharmaceutical manufacturing.

- **Laboratory Consumables:** We supply a wide range of laboratory consumables such as fine ceramic products, electrochemical consumables, PTFE material products, high purity materials, battery materials, chemical vapor deposition materials, optical materials, thin film deposition components and glass materials. These consumables provide the necessary support for laboratories to ensure the smooth running of experimental processes.

Technological Advantages

Kintek Solution Ltd has significant technological strengths in the field of scientific research equipment and technical solutions, which enable us to stand out in a competitive marketplace and support our customers with cutting-edge technology. The following are our key technological strengths:

Advanced R&D capabilities

- **Technological Innovation:** Our R&D team is committed to exploring and developing the latest technologies to keep our equipment at the forefront of the industry through continuous technological innovation.
- **Customized solutions:** Based on the specific needs of our customers, we are able to develop and provide customized equipment to meet specific research requirements and application scenarios.
- **Cooperative R&D:** We cooperate with leading research institutes and higher education institutions around the world to carry out R&D projects on cutting-edge technologies to ensure that our technologies are always at the forefront of the industry.

High-performance equipment

- **Precision design:** Our equipment adopts advanced design concepts to ensure high precision, reliability and performance to meet the stringent requirements of scientific research and industrial applications.
- **Advanced materials:** We use high-quality materials and components to improve the durability and stability of our equipment, extend its service life and reduce maintenance costs.

Strict quality control

- Standardized production: All equipment is manufactured in accordance with international quality standards, and each production step is strictly controlled to ensure product consistency and reliability.
- Comprehensive testing: Comprehensive performance testing and quality inspection are carried out before the equipment is delivered to ensure that it meets the customer's technical specifications and operational requirements.

Comprehensive technical support

- Technical Service: Provide comprehensive technical support and after-sales service, including equipment installation, commissioning, training and maintenance, to ensure that customers can use our products efficiently.
- Rapid Response: We have established a rapid response mechanism, which can promptly solve the problems encountered by customers in the process of use and reduce equipment downtime.

Innovative technology integration

- System Integration: We integrate advanced control systems and automation technologies into our equipment to improve operational efficiency and data accuracy, and streamline operational processes.

Through these technological advantages, Kintek Solution Ltd is able to continue to provide our customers with innovative, efficient and reliable scientific research equipment and solutions to promote the continuous progress of scientific research and industrial applications.

Market position and customers

Kintek Solution Ltd is positioned in the market as a leading global provider of high-tech research equipment and solutions, specializing in biochemical reactions, new materials research, heat treatment, vacuum manufacturing, refrigeration, as well as pharmaceuticals and oil extraction. We are committed to brand leadership in research equipment by providing innovative technology and high quality equipment to meet the needs of research organizations and industrial companies in complex research and production processes.

Core Market Positioning:

- **Specialization:** We focus on high technology and scientific research, providing advanced equipment and solutions for specialized research institutes, laboratories and industrial applications.
- **High-end customers:** Our main customers include world-renowned universities, research institutes and various industrial enterprises, which usually have high requirements for equipment performance and technology.
- **Technological Innovation:** We are committed to technological innovation and customized solutions to ensure that our customers receive cutting-edge technical support to meet the ever-changing needs and challenges in the market.

Market Customer Groups:

- **Research Institutes and Universities:** including the world's leading research institutes and institutions of higher learning, who require high-performance research equipment and technical support for basic research, applied research and technology development.
- **Industrial companies:** covering a wide range of industries such as pharmaceuticals, oil extraction, new materials manufacturing and electronic materials production, these companies rely on reliable equipment and solutions to ensure product quality and productivity during production.
- **Laboratories and test centers:** organizations that provide laboratory services and quality testing, requiring accurate laboratory equipment and instruments for sample analysis and testing.
- **Technology Development Companies:** Companies that specialize in the development and application of new technologies and have a high demand for innovative equipment and technical solutions to support their R&D projects and technology validation.

Through clear market positioning and customer groups, we are committed to promoting scientific and technological progress, supporting the innovation and development of our global customers, and continuing to provide high-quality products and services to the market.

Team Introduction

The team at Kintek Solution Ltd is at the heart of the company's success. In order to realize our vision and maintain our leadership position in the field of high-tech research equipment, we are committed to building an exceptional team with the following attributes:

1. Professionalism

- **Technical Expertise:** Our team consists of technical experts and engineers in the field with deep expertise and technical backgrounds to meet complex technical challenges and innovation needs.
- **Industry experience:** We bring together professionals with extensive experience in the fields of research equipment, material science and engineering technology to ensure a precise grasp of market needs and technological trends.

2. Innovative Spirit

- **R&D-driven:** The team encourages innovative thinking and technological exploration, supports employees to participate in R&D projects on cutting-edge technologies, and continuously pushes forward the technological advancement of products and solutions.
- **Flexible Adaptation:** In the face of changing market environment, we have the ability to adapt quickly and flexibly to meet the changing needs of our customers.

3. Collaboration and Communication

- **Cross-sectoral collaboration:** The team maintains close collaboration between various departments, including R&D, production, sales and customer service, to ensure the smooth progress of projects and timely response to customer needs.
- **Efficient Communication:** Emphasize internal communication and information sharing, through efficient communication mechanisms and tools to ensure that all team members are consistent with the project goals and progress.

4. Customer Orientation

- **Customer Service:** Team members are customer-focused and committed to providing quality service and support to ensure that our customers have the best experience in using our products and solutions.

- Customized solutions: the ability to deeply understand the specific needs of customers and provide customized solutions to meet the special requirements of different customers.

5. Professional Training and Development

- Continuous Learning: We provide continuous training and learning opportunities for our team members to ensure that they are always up-to-date with the latest technology and industry knowledge.
- Career Development: We value the career development and growth of our employees, provide clear career paths and promotion opportunities, and motivate our employees to realize their personal goals and career aspirations within the company.

6. Corporate Culture

- Integrity and Responsibility: The team upholds integrity and responsibility, treats work and customers with honesty and fairness, and builds trust and long-term cooperative relationships.
- Unity and Collaboration: Focusing on the spirit of teamwork, the team emphasizes mutual support and joint efforts to achieve the company's goals and promote the overall success of the team.

By building such a highly qualified, innovation-driven and customer-oriented team, we ensure that Kintek Solution Ltd continues to lead in the field of scientific research equipment and provide excellent products and services to our customers worldwide.

At KINTEK, technology fuels our corporate spirit. This dynamic energy awaits you upon joining our team. Expect a distinctive cultural environment where our global business focus opens doors to diverse customs and traditions worldwide. Here, challenging roles promise to propel your career to new heights.

Our exceptional corporate culture sparks innovation, fosters care, and drives continuous progress among individuals and teams. Our team embodies youthfulness, positivity, enthusiasm, and a bold attitude toward challenges. Passionate about our business, our employees ardently contribute to the company's growth.

We seek individuals brave enough to embrace challenges, harbor grand ambitions, and thirst for knowledge. If you're driven by dreams and passion, and aspire to start your

entrepreneurial journey, KINTEK is the platform to actualize your career plans. We don't just offer opportunities; we pave the way for your future.

Join us at KINTEK, where innovation meets opportunity. Let's create a future that's as promising as your aspirations.

Future Plans

Kintek Solution Ltd's future plans are aimed at further strengthening our leadership position in the research equipment sector and driving the company forward in terms of technological innovation, market expansion and customer service. The following are our key future directions:

1. Technology Innovation and R&D

- Cutting-edge technology development: Continue to invest resources in the research and development of cutting-edge technologies, such as artificial intelligence, the Internet of Things and nanotechnology, in order to promote equipment intelligence and automation.
- New Product Lines: Expand existing product lines and develop equipment to meet emerging market needs, especially in the areas of biochemistry, biomedicine and high-performance materials.
- Cooperative R&D: Strengthen cooperation with international research institutes and institutions of higher learning to carry out joint R&D projects to ensure that the technology remains at the global leading level.

2. Market Expansion

- Global Market Expansion: Further expand the global market, especially in emerging markets and developing regions, establish more sales and service networks, and enhance the brand's international influence.
- Industry application: Explore and expand the application fields in other industries, such as new energy, environmental protection technology and intelligent manufacturing, to open up new business growth points.

3. Customer Service Enhancement

- Enhancement of customer support: Establish a more complete customer support system, provide 24/7 technical support and maintenance services, and ensure

the efficient experience of customers in the use of equipment.

- Customized services: Provide more customized services and solutions according to customers' individual needs to enhance customer satisfaction and loyalty.

4. Sustainable Development

- Environmentally friendly technology: Develop and adopt environmentally friendly materials and processes to reduce the environmental impact during the production and use of equipment and promote sustainable development.
- Energy saving and consumption reduction: Optimize the energy efficiency of equipment, reduce energy consumption, improve resource utilization efficiency, and support the development of green technology.

5. Internal optimization

- Intelligent management: Implement intelligent management systems and data analysis tools to improve productivity and management and reduce operating costs.
- Employee Training: Enhance employee training and skills upgrading to build a high-quality team to meet changing market demands and technological challenges.

6. Innovation ecosystem

- Establishment of innovation platform: Create innovation platforms and laboratories to support employees and partners in technological innovation and product development.
- Industry Chain Cooperation: Deepen cooperation with the upstream and downstream of the industry chain, integrate resources, and promote the development and implementation of industry technical standards and market norms.

Through these future plans, Kintek Solution Ltd will continue to lead the forefront of science and technology, provide customers with more advanced and reliable products and services, and at the same time, promote the sustainable development of the enterprise and the progress of the industry.



Manual Lab Hydraulic Pellet Press 12T / 15T / 24T / 30T / 40T

Item Number: PCMP

Introduction

Efficient sample preparation with small footprint Manual Lab Hydraulic Press. Ideal for material researching labs, pharmacy, catalytic reaction, and ceramics.

[Learn More](#)



Instrument model	PCMP-2T	PCMP-5T	PCMP-12T
Pressure range	0-2T (25MPa)	0-5T(0-31.4MPa)	0-12T(0-30MPa)
Piston diameter	Φ32mm (d)	Φ45mm (d)	Φ70mm (d)
Integral structure	No sealing connection, oil leakage reduced	No sealing connection, oil leakage reduced	No sealing connection, oil leakage reduced
Pressure gauge	Pressure and pressure intensity display	Pressure and pressure intensity display	Pressure and pressure intensity display
Maximum pressure (T)	30mm	30mm	30mm
Pressure stability	≤1MPa/10min	≤1MPa/10min	≤1MPa/10min
Workbench diameter	Φ50mm (D)	Φ80mm (D)	Φ80mm (D)
Number of columns	Two	Two	Two
Working space	85×120mm(M×N)	96×130mm(M×N)	96×130mm(M×N)
Dimensions	210×150×350mm(L×W×H)	225×155×380mm(L×W×H)	225×155×380mm(L×W×H)
Weight	12 Kg	28Kg	28Kg

Electric Hydraulic Pellet Press For Xrf & Kbr 20T / 30T / 40T / 60T

Item Number: PCPE



Introduction

Efficiently prepare samples with the Electric Hydraulic Press. Compact and portable, it's perfect for labs and can work in a vacuum environment.

[Learn More](#)

Instrument model	PCPE-20T	PCPE-30T	PCPE-40T	PCPE-60T
Pressure range	0-20T(0-28MPa)	0-30T(0-31.5MPa)	0-40T(0-30MPa)	0-60T(0-33MPa)
Piston diameter	Φ95mm (d)	Φ110mm (d)	Φ130mm (d)	Φ150mm (d)
Integral structure	No sealing connection, oil leakage reduced	No sealing connection, oil leakage reduced	No sealing connection, oil leakage reduced	No sealing connection, oil leakage reduced
Pressure gauge	Digital display 0.00-40.00 MPa	Digital display 0.00-40.00 MPa	Digital display 0.00-40.00 MPa	Digital display 0.00-40.00 MPa
Maximum pressure (T)	30mm	40mm	50mm	50mm
Pressure stability	≤1MPa/10min	≤1MPa/10min	≤1MPa/10min	≤1MPa/10min
Pressurization mode	Electric / manual	Electric / manual	Electric / manual	Electric / manual
Compensation mode	Auto/ manual	Auto/ manual	Auto/ manual	Auto/ manual
Workbench diameter	Φ105mm (D)	Φ120mm (D)	Φ140mm(D)	Φ160mm (D)
Number of columns	Four	Four	Four	Four
Working space	80×150mm(M×N)	92×160mm(M×N)	115×185mm(M×N)	185×250mm(M×N)
Dimensions	245×415×415mm(L×W×H)	275×430×420mm(L×W×H)	295×450×500mm(L×W×H)	405×470×565mm(L×W×H)
Power supply	220V(50Hz/60Hz)	220V(50Hz/60Hz)	220V(50Hz/60Hz)	220V(50Hz/60Hz)
Weight	58Kg	72Kg	92Kg	140Kg

Force	Pressure
1 [Tons]	1.41 [MPa]
2 [Tons]	2.82 [MPa]
3 [Tons]	4.23 [MPa]
5 [Tons]	7.06 [MPa]
8 [Tons]	11.3 [MPa]
10 [Tons]	14.1 [MPa]
12 [Tons]	17 [MPa]
15 [Tons]	22.6 [MPa]

20 [Tons]

28 [MPa]

Note: The system pressure intensity shouldn't exceed 35 MPa, or else it will shorten the service life of the equipment.

Electric Lab Cold Isostatic Press (Cip) 12T / 20T / 40T / 60T

Item Number: PCIE



Introduction

Produce dense, uniform parts with improved mechanical properties with our Electric Lab Cold Isostatic Press. Widely used in material research, pharmacy, and electronic industries. Efficient, compact, and vacuum-compatible.

[Learn More](#)

Instrument model	PCIE-12T	PCIE-20T	PCIE-40T	PCIE-60T
Pressure Range	0-12T(0-17MPa)	0-20T(0-21MPa)	0-40T(0-30MPa)	0-60T(0-34MPa)
Piston diameter	95mm (d) in chrome plated oil cylinder	110mm (d) in chrome plated oil cylinder	130mm (d) in chrome plated oil cylinder	150mm (d) in chrome plated oil cylinder
Pressure gage	Digital display0.0-40.0MPa	Digital display0.0-40.0MPa	Digital display0.0-40.0MPa	Digital display0.0-40.0MPa
Maximum piston stroke (T)	40mm	40mm	50mm	50mm
Way of Pressure	Electric pressurization/manual pressurization	Electric pressurization/manual pressurization	Electric pressurization/manual pressurization	Electric pressurization/manual pressurization
Pressure replenishment method	Automatic pressurization/manual slow pressurization	Automatic pressurization/manual slow pressurization	Automatic pressurization/manual slow pressurization	Automatic pressurization/manual slow pressurization
guard	Organic glass	Organic glass	Organic glass	Organic glass
ambient temperature	10°C-40°C	10°C-40°C	10°C-40°C	10°C-40°C
Isostatic pressure	0-300MPa	0-300MPa	0-300MPa	0-300MPa
Isostatic pressure chamber	Φ22×70mm(M×N)	Φ30×120mm(M×N)	Φ40×150mm(M×N)	Φ50×150mm(M×N)
External dimensions	305×430×530mm(L×W×H)	305×430×600mm(L×W×H)	355×450×710mm(L×W×H)	405×470×720mm(L×W×H)
power supply	550W(220V/110 can be customized)	550W(220V/110 can be customized)	550W(220V/110 can be customized)	550W(220V/110 can be customized)
Equipment weight	110Kg	120Kg	150Kg	200Kg

Hydraulic Heated Lab Pellet Press 24T / 30T / 60T

Item Number: PCH



Introduction

Looking for a reliable Hydraulic Heated Lab Press? Our 24T / 40T model is perfect for material research labs, pharmacy, ceramics, and more. With a small footprint and the ability to work inside a vacuum glove box, it's the efficient and versatile solution for your sample preparation needs.

[Learn More](#)

Instrument model	PCH-24T1010	PCH-30T2020	PCH-60T1818
Pressure Range	0-24.0 tons	0-30.0 tons	0-60.0 tons
piston diameter	95mm (d) in chrome plated oil cylinder	110mm (d) in chrome plated oil cylinder	150mm (d) in chrome plated oil cylinder
Main overall structure	Equipment without sealed connections to reduce oil leakage points	Equipment without sealed connections to reduce oil leakage points	Equipment without sealed connections to reduce oil leakage points
Mold heating temperature	Room temperature-300.0C/500.0C	Room temperature -300.0C/500.0C	Room temperature-300.0C/500.0C
Insulation method	Imported insulation board	Imported insulation board	Imported insulation board
Cooling method	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]
Hot platen size	100×100mm (M×N)with chamfer	200×200mm(M×N)	180×180mm (M×N)
Host size	245×175×500mm(K×P×H)	405×260×525mm(K×P×H)	405 ×260×525mm(K×P×H)
Dimensions	500×175×500mm(L×W×H)	950×260×525mm(L×W×H)	950×260×525mm(L×W×H)
power supply	600 W(220V/110V can be customized)	1200 W(220V/110V can be customized)	1000 W(220V/110V can be customized)
Weight	60 Kg	180 Kg	180 Kg

Button Battery Press 5T

Item Number: PCBP

Introduction

Efficiently prepare samples with our 5T Button Battery Press. Ideal for material research labs and small-scale production. Small footprint, lightweight, and vacuum-compatible.

[Learn More](#)



Instrument model	PCBP-2T (Manual)	Instrument model	PCBP-1.5T(Automatic)
Pressure range	0-2T (0-25MPa)	Pressure Range	50-1500kg
Piston diameter	Φ32mm (d)	Pressurization process	Program pressurization-program pressure-timed pressure relief
Integral structure	No sealing connection, oil leakage reduced	Pressure retention time	0-999 seconds
Pressure gauge	Pressure and pressure intensity display	Pressure conversion	The program automatically converts the mold to withstand pressure
Standard die	CR20 series packaging die	LCD display	4.3-inch LCD screen
Sealing die	CR16,CR20,CR24,CR30optional	Sealing mold	Optional CR16,CR20,CR24,CR30,etc
Sealing pressure	0.8-1.2Ton	Shell removal mold	Optional CR16,CR20,CR24,CR30,etc
Disassembly die	CR16,CR20,CR24 optional	Standard mold	Standard CR20 series packaging mold
Disassembly pressure		External dimensions	220x240x380(LXWXH)
Dimensions	210×165×290mm(L×W×H)	Equipment power supply	220V(50Hz/60Hz)
Weight	12Kg	Equipment weight	35kg

Manual Lab Hydraulic Pellet Press With Safety Cover 15T / 24T / 30T / 40T / 60T

Item Number: PCF



Introduction

Efficient Manure Lab Hydraulic Press with Safety Cover for sample preparation in material research, pharmacy, and electronic industries. Available in 15T to 60T.

[Learn More](#)

Instrument model	PCF-15T
Pressure range	0-15T(0-30MPa)
Piston diameter	Φ80mm (d)
Pressure gauge	Pressure and pressure intensity display
Maximum pressure (T)	30mm
Protective cover	Plexiglass
Pressure stability	≤1MPa/10min
Workbench diameter	Φ90mm (D)
Number of columns	Four
Working space	80×130mm(M×N)
Dimensions	260×175×395mm(L×W×H)
Weight	42Kg
Force	Pressure
1[Tons]	0.75[MPa]
3[Tons]	2.2[MPa]
5 [Tons]	3.7[MPa]
10[Tons]	7.5[Mpa]

12[Tons]	9[MPa]
15[Tons]	11.3[MPa]
20[Tons]	15[MPa]
30[Tons]	22.5[MPa]
40[Tons]	30[MPa]

Note: The system pressure intensity shouldn't exceed 35 MPa, or else it will shorten the service life of the equipment.

Integrated Manual Heated Lab Pellet Press 120Mm / 180Mm / 200Mm / 300Mm

Item Number: PCY



Introduction

Efficiently process heat-pressing samples with our Integrated Manual Heated Lab Press. With a heating range up to 500°C, it's perfect for various industries.

[Learn More](#)

Instrument model	PCY-5T1212	PCY-10T1818	PCY-10T2020	PCY-15T3030
Pressure Range	0-5.0 tons	0-10.0 tons	0-10.0 tons	0-15.0 tons
Piston diameter	50mm (d) in chrome plated oil cylinder	65mm (d) in chrome plated oil cylinder	65mm (d) in chrome plated oil cylinder	95mm (d) in chrome plated oil cylinder
Main overall structure	Equipment without sealed connections to reduce oil leakage points	Equipment without sealed connections to reduce oil leakage points	Equipment without sealed connections to reduce oil leakage points	Equipment without sealed connections to reduce oil leakage points
Mold heating temperature	Room temperature -300.0C/500.0C	Room temperature-300.0C/500.0C	Room temperature-300.0C/500.0C	Room temperature-300.0C/500.0C
Insulation method	Imported insulation board	Imported insulation board	Imported insulation board	Imported insulation board
Cooling method	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]
Hot platen size	Double plate heating 120×120mm(M×N)	Double plate heating 180×180mm(M×N)	Double plate heating 200×200mm(M×N)	Double plate heating 300×300mm(M×N)
Workspace	140×140×60mm	180×180×60mm	200×200×60 mm	300×300×65mm
Dimensions	250×230×390mm(L×W×H)	290×290×420mm(L×W×H)	320×290×420mm(L×W×H)	450×420×450mm(L×W×H)
Power supply	700W(220V/110V can be customized)	1000 W(220V/110V can be customized)	1200 W(220V/110V can be customized)	3000 W(220V/110V can be customized)
Weight	55 Kg	90 Kg	95Kg	180Kg
Dimensional diagram of powder tablet press	See picture below	See picture below	See picture below	See picture below

Split Manual Heated Lab Pellet Press 30T / 40T

Item Number: PCSM



Introduction

Efficiently prepare your samples with our Split Manual Heated Lab Press. With a pressure range up to 40T and heating plates up to 300°C, it's perfect for various industries.

[Learn More](#)

Instrument model	PCSM-30T3030	PCSM-40T4040
Pressure Range	0-30.0 tons	0-40.0 tons
Piston diameter	130mm (d) in chrome plated oil cylinder	130mm (d) in chrome plated oil cylinder
Main overall structure	Equipment without sealed connections to reduce oil leakage points	Equipment without sealed connections to reduce oil leakage points
Mold heating temperature	Room temperature-300.0C/500.0C	Room temperature-300.0C
Insulation method	Imported insulation board	Imported insulation board
Cooling method	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]
Hot platen size	300×300mm (M×N)	400×400mm(M×N)
Host size	380×350×600mm(K×P×H)	500×480×650(K×P×H)
Dimensions	700×400×600mm(L×W×H)	800×480×650(L×W×H)
Power supply	3000 W(220V/110V can be customized)	5000 W(220V/110V can be customized)
Weight	260 Kg	460Kg
Dimensional diagram of powder tablet press	See picture below	See picture below

Split Automatic Heated Lab Pellet Press 30T / 40T

Item Number: PCSE



Introduction

Discover our split automatic heated lab press 30T/40T for precise sample preparation in material research, pharmacy, ceramics, and electronics industries. With a small footprint and heating up to 300°C, it's perfect for processing under vacuum environment.

[Learn More](#)

Instrument model	PCSE-40T4040	PCSE-30T3030
Pressure Range	0-40.0 tons	0-30.0tons
Pressurization process	Program pressurization - Program holding -Timed pressure relief	Program pressurization - Program holding - Timed
Mold heating temperature	Room temperature-300.0C	Room temperature -300.0C/500.0C
Insulation method	Imported insulation board	Imported insulation board
Cooling method	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]
Hot platen size	400×400mm(M×N)	300×300mm(M×N)
Host size	500×480X650(K×P×H)	380×350×600mm(K×P×H)
Dimensions	850×480X650(L×W×H)	700×400×600mm(L×W×H)
Powersupply	5500W(220V/110V can be customized)	3500W(220V/110V can be customized)
Weight	480 Kg	280 Kg

Automatic Heated Lab Pellet Press 25T / 30T / 50T

Item Number: PCAH



Introduction

Efficiently prepare your samples with our Automatic Heated Lab Press. With a pressure range up to 50T and precise control, it's perfect for various industries.

[Learn More](#)

Instrument Model	PCAH-5T1212/1212G	PCAH-25T1818/1818G	PCAH-25T2020/2020G	PCAH-30T3030/3030G	PCAH-40T4040/4040G
Pressure Range	0-5.0 tons	0-25.0 tons	0-25.0 tons	0-30.0 tons	0-40.0 tons
Pressurization Process	Program pressurization - Program holding - Timed pressure relief	Program pressurization - Program holding - Timed pressure relief	Program pressurization - Program holding - Timed pressure relief	Program pressurization - Program holding - Timed pressure relief	Program pressurization - Program holding - Timed pressure relief
Mold Heating Temperature	Room temperature-300.0°C/500.0°C	Room temperature-300.0°C/500.0°C	Room temperature-300.0°C/500.0°C	Room temperature-300.0°C/500.0°C	Room temperature-300.0°C
Insulation Method	Imported insulation board	Imported insulation board	Imported insulation board	Imported insulation board	Imported insulation board
Cooling Method	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]	Quick cooling with water cooling [optional water cooling machine]
Hot platen size	120X120mm(M×N)	180×180mm(M×N)	200×200mm(M×N)	300×300mm(M×N)	400X400mm(M×N)
Dimensions	182×306×460mm(L×W×H)	300×390×560mm(L×W×H)	300×390×560mm(L×W×H)	400×490×580mm(L×W×H)	500×550×620mm(L×W×H)
Powersupply	900 W(220V/110V can be customized)	1700 W (220V/110V can be customized)	1700 W(220V/110V can be customized)	3500 W(220V/110V can be customized)	5500 W (220V/110V can be customized)
Weight	75 Kg	140 Kg	140 Kg	280 Kg	480 Kg

Automatic Lab Xrf & Kbr Pellet Press 30T / 40T / 60T

Item Number: PMXA



Introduction

Fast and easy xrf sample pellet preparation with KinTek Automatic Lab Pellet Press. Versatile and accurate results for X-ray fluorescence analysis.

[Learn More](#)

Instrument model	PMXA-30T	PMXA-40T	PMXA-60T
Pressure Range	1-30.0 tons	0-40.0 tons	0-60.0 tons
Pressurization process	Program pressurization - Program pressure maintaining - Timed pressure relief-Automatic sample withdrawal	Program pressurization - Program pressure maintaining -Timed pressure relief-Automatic sample withdrawal	Program pressurization - Program pressure maintaining - Timed pressure relief-Automatic sample withdrawal
Hold time	1 second to 0 seconds	1 second to 0 seconds	1 second to 0 seconds
Pressure conversion	Program automatically converts the pressure borne by the mold	Program automatically converts the pressure borne by the mold	Program automatically converts the pressure borne by the mold
Display	4.3 inch LCD screen	4.3 inch LCD screen	4.3 inch LCD screen
Metal buttons	Silver plated contacts with a service life of over100000 times	Silver plated contacts with a service life of over100000 times	Silver plated contacts with a service life of over100000 times
Built in mold	Boric acid/steel ring/plastic ring mold (built-in 1 set of mold)	Boric acid/steel ring/plastic ring mold (built-in 1 'set of mold)	Boric acid/steel ring/plastic ring mold (built-in 1 set of mold)
Sample size	Sample size standard configuration 40mm	Sample size standard configuration40mm	Sample size standard configuration40mm
Mold material	440C mold steel	440C mold steel	440C mold steel
Demoulding method	Automatic stripping	Automatic stripping	Automatic stripping
External dimensions	250×390×460mm(L×W×H)	280×460×550mm(L×W×H)	300×520×580mm(L×W×H)
Equipment power supply	550W (220V/110 can be customized)	550W(220V/110 can be customized)	550W(220V/110 can be customized)
Equipment weight	120Kg	150Kg	180Kg
Dimensional diagram of powder tablet press	See picture below	See picture below	See picture below

Manual Cold Isostatic Pellet Press (Cip) 12T / 20T / 40T / 60T

Item Number: PCIM



Introduction

Lab Manual Isostatic Press is a high-efficient equipment for sample preparation widely used in material research, pharmacy, ceramics, and electronic industries. It allows for precision control of the pressing process and can work in a vacuum environment.

[Learn More](#)

Instrument model	PCIM-12T	PCIM-20T	PCIM-40T	PCIM-60T
Pressure Range	0-12T(0-17MPa)	0-20T(0-21MPa)	0-40T(0-30MPa)	0-60T(0-34MPa)
Piston diameter	95mm (d) in chrome plated oil cylinder	110mm (d) in chrome plated oil cylinder	130mm (d) in chrome plated oil cylinder	150mm (d) in chrome plated oil cylinder
Pressure gage	Pressure and pressure dual scale display	Pressure and pressure dual scale display	Pressure and pressure dual scale display	Pressure and pressure dual scale display
Maximum piston stroke (T)	40mm	40mm	50mm	50mm
Guard	Organic glass	Organic glass	Organic glass	Organic glass
Ambient temperature	10°C-40°C	10°C-40°C	10°C-40°C	10°C-40°C
Isostatic pressure	0-300MPa	0-300MPa	0-300MPa	0-300MPa
Isostatic pressure chamber	Φ22×70mm(M×N)	Φ30×120mm(M×N)	Φ40×150mm(M×N)	Φ50×150mm(M×N)
External dimensions	305×195×530mm(L×W×H)	305×195×600mm(L×W×H)	355×215×710mm(L×W×H)	405×240×720mm(L×W×H)
Equipment weight	90Kg	100Kg	130Kg	180Kg

Pressure conversion		
Actual pressure	Chamber pressure	System pressure
1.7 [Tons]	1.86 [MPa]	25 [MPa]
3.5 [Tons]	3.72 [MPa]	50 [MPa]
5 [Tons]	5.57 [MPa]	75 [MPa]
7 [Tons]	7.43 [MPa]	100 [MPa]
8.7 [Tons]	9.29 [MPa]	125 [MPa]
10.5 [Tons]	11.2 [MPa]	150 [MPa]
14 [Tons]	14.8 [MPa]	200 [MPa]
17.5 [Tons]	18.6 [MPa]	250 [MPa]
21 [Tons]	22.3 [MPa]	300 [MPa]

Reminder: Generally, the system pressure should not exceed 35MPa, otherwise it will affect the service life of the equipment.

Electric Split Lab Cold Isostatic Press (Cip) 65T / 100T / 150T / 200T

Item Number: PCESI



Introduction

Split cold isostatic presses are capable of providing higher pressures, making them suitable for testing applications that require high pressure levels.

[Learn More](#)

Instrument model	PCESI-65T	PCESI-100T	PCESI-150T	PCESI-200T
Pressure Range	0-65T	0-100T	0-150T	0-200T
Piston diameter	160mm (d) in chrome plated oil cylinder	200mm (d) in chrome plated oil cylinder	200mm (d) in chrome plated oil cylinder	290mm (d) in chrome plated oil cylinder
Pressurization process	Program pressurization - Program holding -Timed pressure relief	Program pressurization -Program holding -Timed pressure relief	Program pressurization - Program holding-Timed pressure relief	Program pressurization - Program holding -Timed pressure relief
Pressure conversion	The program automatically converts the pressure borne by the sample	The program automatically converts the pressure borne by the sample	The program automatically converts the pressure borne by the sample	The program automatically converts the pressure borne by the sample
Display	7-inch LCD screen	7-inch LCD screen	7-inch LCD screen	7-inch LCD screen
Equipment protection	Steel plate protection with organicglass door	Steel plate protection with organicglass door	Steel plate protection with organic glass door	Steel plate protection with organicglass door
Isostatic pressure	0-300MPa	0-300MPa	0-300MPa	0-300MPa
Isostatic pressure chamber	Φ50×150mm(M×N)	Φ60×150mm(M×N)	Φ80×150mm(M×N)	Φ90×150mm(M×N)
Cylinder stroke (T)	50mm	50mm	50mm	50mm
Space size	220×400mm(M×N)	260×400mm(M×N)	280×400mm(M×N)	290×420mm(M×N)
External dimensions	700×450×1050mm(L×W×H)	850×500×1100mm(L×W×H)	950×550×1150mm(L×W×H)	1000×650×1200mm(L×W×H)
Equipment power supply	1500W(220V/110 can be customized)	1500W (220V/110 can be customized)	1500W(220V/110 can be customized)	1500W(220V/110 can be customized)
Equipment weight	350kg	580kg	680kg	980kg

Automatic Lab Cold Isostatic Press (Cip) 300Mpa-400Mpa-500Mpa

Item Number: PCIA



Introduction

Efficiently prepare samples with our Automatic Lab Cold Isostatic Press. Widely used in material research, pharmacy, and electronic industries. Provides greater flexibility and control compared to electric CIPs.

[Learn More](#)

Instrument model	PCIA-20T	PCIA-40T	PCIA-60T	PCIA-100T
Piston diameter	110mm (d) in chrome plated oil cylinder	130mm (d) in chrome plated oil cylinder	150mm (d) in chrome plated oil cylinder	200mm (d) in chrome plated oil cylinder
Pressurization process	Program pressurization - Program holding -Timed pressure relief	Program pressurization - Program holding -Timed pressure relief	Program pressurization - Program holding -Timed pressure relief	Program pressurization - Program holding -Timed pressure relief
Pressure conversion	The program automatically converts the pressure borne by the sample	The program automatically converts the pressure borne by the sample	The program automatically converts the pressure borne by the sample	The program automatically converts the pressure borne by the sample
Display	4.3 inch LCD screen	4.3 inch LCD screen	4.3 inch LCD screen	7 inch LCD screen
Equipment protection	Steel plate protection with organicglass door	Steel plate protection with organic glass door	Steel plate protection with organic glass door	Steel plate protection with organic glass door
Isostatic pressure	300-500MPA	300-500MPA	300-500MPA	300-500MPA
Isostatic pressure chamber	Φ30×150mm(M×N)	Φ40×150mm(M×N)	Φ50×150mm/30×150mm	Φ60×150(M×N)
Cylinder stroke (T)	50mm	50mm	50mm	50mm
Sample making characteristics	Upperpanel rocker arm structure formore convenient operation	Upperpanel rocker arm structure formore convenient operation	Upperpanel rocker arm structure formore convenient operation	Upperpanel rocker arm structure formore convenient operation
External dimensions	240×390×560(L×W×H)	280×460×660(L×W×H)	/	330×580×720(L×W×H)
Equipment power supply	550W(220V/110 can be customized)	550W(220V/110 can be customized)	550W(220V/110 can be customized)	550W(220V/110 can be customized)
Equipmentweight	120KG	180KG	240KG	290KG

Warm Isostatic Press (Wip) Workstation 300Mpa

Item Number: PCIW



Introduction

Discover Warm Isostatic Pressing (WIP) - A cutting-edge technology that enables uniform pressure to shape and press powdered products at a precise temperature. Ideal for complex parts and components in manufacturing.

[Learn More](#)

Model	Cylinder inner diameter (mm)	Cylinder inner height (mm)	Maximum pressure (MPa)	Maximum temperature
PCIW150	Ø150	300-500	300	(Deionized water) ≤ 90°C (heat transfer oil) ≤ 250°C
PCIW200	Ø200	500-1000		
PCIW250	Ø250			
PCIW300	Ø300			
PCIW350	Ø350	500-1500		
PCIW400	Ø400	500-2000		
PCIW450	Ø450			
PCIW500	Ø500	1000-3000		
PCIW630	Ø630			
PCIW710	Ø710			
PCIW800	Ø800			
PCIW910	Ø910			
PCIW1000	Ø1000			

Lab Pellet Press For Vacuum Box

Item Number: PCV



Introduction

Enhance your lab's precision with our lab press for vacuum box. Press pills and powders with ease and precision in a vacuum environment, reducing oxidation and improving consistency. Compact and easy to use with a digital pressure gauge.

[Learn More](#)

Instrument model	PCV-10T1818	PCV-10T2020
Pressure Range	0-10.0 tons	0-10.0 tons
Pressurization process	Manual pressurization	Manual pressurization
Heating temperature	Maximum 500°C	Maximum 500°C
Heating plate	180×180mm	200×200mm
Vacuum box material	SUS 304 (stainless steel)	SUS 304 (stainless steel)
Studio Size	400×400×400mm	400×100×400mm
Door size	300×350mm	300×350mm
Vacuum degree	-0.1MPa	-0.1MPa
Dimensions	450×550×850(L×W×H)	450×550×850(L×W×H)
Power supply	220V50Hz (can support 110V)	220V50Hz (can support 110V)

Lab Pellet Press Machine For Glove Box

Item Number: PCG



Introduction

Controlled environment lab press machine for glove box. Specialized equipment for material pressing and shaping with high precision digital pressure gauge.

[Learn More](#)

Instrument model	PCG-25T1818	PCG-25T2020
Pressure Range	0-25T	0-25T
Pressurization process	Program pressurization-program pressure-timed pressure relief	Program pressurization-program pressure-timed pressure relief
Pressure retention time	0-999.59(point.Seconds)	0-999.59(point.Seconds)
Heating temperature	Up to 500°C	Up to 500°C
Heating plate	180×180mm	200×200mm
Glove box handle	St's 304	St's 304
Studio size	780×650×700	780×650×700
Transition cabin size	Φ240×260mm	Φ240×260mm
Vacuum degree	-0.1MPa	-0.1MPa
Size of the whole machine	1200×950×1800(L×W×H)	1200×950×1800(L×W×H)
Power supply	220V 50Hz	220V 50Hz

Split Electric Laboratory Pellet Press 40T / 65T / 100T / 150T / 200T

Item Number: PCES



Introduction

Efficiently prepare samples with a split electric lab press - available in various sizes and ideal for material research, pharmacy, and ceramics. Enjoy greater versatility and higher pressure with this portable and programmable option.

[Learn More](#)

Instrument model	PCES-40T	PCES-65T	PCES-100T	PCES-150T	PCES-200T
Pressure Range	0-40 tons	0-65tons	1-100tons	1-150tons	1-200tons
Piston diameter	130mm (d)	160mm (d)	200mm (d)	250mm (d)	290mm (d)
Pressurization process	Program pressurization	Program pressurization	Program pressurization	Program pressurization	Program pressurization
Pressure conversion	Automatically converted pressure	Automatically converted pressure	Automatically converted pressure	Automatically converted pressure	Automatically converted pressure
Display	7-inch LCD	7-inch LCD	7-inch LCD	7-inch LCD	7-inch LCD
Equipment protection	Steel plate protection with organic glass door	Steel plate protection with organic glass door	Steel plate protection with organic glass door	Steel plate protection with organic glass door	Steel plate protection with organic glass door
Cylinder stroke (T)	50mm	50mm	50mm	50mm	50mm
Space size	160×300mm(M×N)	220×300mm(M×N)	260×250mm(M×N)	285×290mm(M×N)	290×300mm(M×N)
External dimensions	500×700×800mm(L×W×H)	580×700×800mm(L×W×H)	850×500×950mm(L×W×H)	950×600×1000mm(L×W×H)	1000×650×1050mm(L×W×H)
Power supply	1500W(220V/110V)	1500W(220V/110V)	1500W(220V/110V)	1500W(220V/110V)	1500W(220V/110V)
Weight	200kg	280kg	520kg	620kg	850kg

Automatic Lab Pellet Press Machine 20T / 30T / 40T / 60T / 100T

Item Number: PCEA



Introduction

Experience efficient sample preparation with our Automatic Lab Press Machine. Ideal for material research, pharmacy, ceramics, and more. Features a compact size and hydraulic press functionality with heating plates. Available in various sizes.

[Learn More](#)

Instrument model	PCEA-12T	PCEA-20T	PCEA-30T	PCEA-40T	PCEA-60T	PCEA-100T
Pressure Range	0.2-12.0 tons	1-20.0 tons	1-30.0 tons	1-40.0 tons	1-60.0 tons	1-100.0 tons
Pressure conversion	Program automatically converts the pressure borne by the mold	Program automatically converts the pressure borne by the mold.	Program automatically converts the pressure borne by the mold	Program automatically converts the pressure borne by the mold	Program automatically converts the pressure borne by the mold	Program automatically converts the pressure borne by the mold
Display	4.3 inch LCD screen	4.3 inch LCD screen	4.3 inch LCD screen	4.3 inch LCD screen	7 inch LCD screen	7 inch LCD screen
Metal buttons	Silver plated contacts with a service life of over 100000	Silver plated contacts with a service life of over 100000 times	Silver plated contacts with a service life of over 100000 times	Silver plated contacts with a service life of over 100000 times	Silver plated contacts with a service life of over 100000 times	Silver plated contacts with a service life of over 100000 times
Equipment protection	Steel plate protection with organic glass door	Steel plate protection with organic glass door	Steel plate protection with organic glass door	Steel plate protection with organic glass door	Steel plate protection with organic glass door	Steel plate protection with organic glass door
Limit switch	Automatic pressure relief when the oil cylinder reaches the limit height	Automatic pressure relief when the oil cylinder reaches the limit height.	Automatic pressure relief when the oil cylinder reaches the limit height	Automatic pressure relief when the oil cylinder reaches the limit height	Automatic pressure relief when the oil cylinder reaches the limit height	Automatic pressure relief when the oil cylinder reaches the limit height
Cylinder stroke (T)	30mm	30mm	30mm	50mm	50mm	50mm
Space size	110×140mm (M×N)	140×160 mm (M×N)	140×160 mm(M×N)	175×180mm(M×N)	185×220mm(M×N)	185×250mm(M×N)
External dimensions	185×320×360 mm (L×W×H)	230×390×420mm(L×W×H)	230×390×420mm(L×W×H)	280×460×550mm(L×W×H)	300×520×580mm(L×W×H)	330×580×620mm(L×W×H)
Equipment power supply	240W(220V/110 can be customized)	550W(220V/110 can be customized)	550W(220V/110 can be customized)	550W (220V/110 can be customized)	550W(220V/110 can be customized)	1500W(220V/110 can be customized)
Equipment weight	50 Kg	90Kg	90Kg	150Kg	180Kg	240Kg

Kbr Pellet Press 2T

Item Number: PCKBR



Introduction

Introducing the KINTEK KBR Press - a handheld laboratory hydraulic press designed for entry-level users.

[Learn More](#)

Model	PCKBR-2T
Working pressure(T)	0-2(30Mpa)
Piston diameter	≤1MPa/10min
Workbench diameter	Φ45mm(D)
Number of columns	Two
Working space	54×55 (M×N)
Dimensions	100×220×220(W×L×H)
Weight(kg)	4.8kg

Automatic Lab Warm Isostatic Press (Wip) 20T / 40T / 60T

Item Number: PCIH



Introduction

Discover the efficiency of Warm Isostatic Press (WIP) for uniform pressure on all surfaces. Ideal for electronics industry parts, WIP ensures cost-effective, high-quality compaction at low temperatures.

[Learn More](#)

Instrument model	PCIH-20T	PCIH-40T	PCIH-60T
Pressure Range	0-20T	0-40T	0-60.0 tons
Piston diameter	130mm (d) in chrome plated oil cylinder	150mm (d) in chrome plated oil cylinder	200mm (d) in chrome plated oil cylinder
Pressurization process	Program pressurization - Program holding-Timed pressure relief		
Hold time	1 second to 0 seconds	1 second to 0 seconds	1 second to 0 seconds
Pressure conversion	The program automatically converts the pressure borne by the sample		
Display	4.3 inch LCD screen	7 inch LCD screen	7 inch LCD screen
Heating temperature	Room temperature-200.0C	Room temperature-200.0C	Room temperature-200.0C
Isostatic pressure	300MPa	300MPa	300MPa
Isostatic pressure chamber	Φ30×150mm(M×N)	Φ40×150mm(M×N)	Φ×50×150 (M×N)
Cylinder stroke (T)	50mm	50mm	50mm
Sample making characteristics	Upperpanel rocker arm structure formore convenient operation		
External dimensions	280×460×660(L×W×H)	280×460×660(L×W×H)	330×580×720(L×W×H)
Equipment power supply	1800W(220V/110 can be customized)	1800W(220V/110 can be customized)	3000W(220V/110 can be customized)
Equipmentweight	180Kg	180Kg	290KG

Manual Lab Pellet Press For Vacuum Box

Item Number: PCVM



Introduction

The lab press for vacuum box is a specialized piece of equipment designed for laboratory use. Its main purpose is to press pills and powders according to specific requirements.

[Learn More](#)

Instrument model	PCVM-10T
Pressure Range	0-10.0 tons
Pressurization process	Manual pressurization
Heating temperature	Maximum 500°C
Heating plate	180x180mm□200x200mm
Vacuum box material	SUS 304 (stainless steel)
Studio Size	400x400x400mm
Door size	300x350mm
Vacuum degree	-0.1MPa
Dimensions	450x550x850(LxWxH)
powersupply	220V50Hz (can support 110V)

Electric Vacuum Heat Press

Item Number: PPZ



Introduction

The Electric Vacuum Heat Press is a specialized heat press equipment that operates in a vacuum environment, utilizing advanced infrared heating and precise temperature control for high quality, rugged and reliable performance.

[Learn More](#)

Instrument model	PPZ-600
Pressure Range	0-25T
Pressurization process	Program pressurization-program pressure-timed pressure relief
Pressure retention time	1 second~0 seconds
Heating temperature	Up to 500°C
Cooked tablet	180x180mm□200x200mm
Vacuum box material	SUS 304 (stainless steel)
Studio size	400x400x400mm
Door size	300x350mm
Vacuum degree	-0.1MPa
Size of the whole machine	450x550x850(LxWxH)
power supply	220V50Hz(support110V)
Dimensional diagram of powder tablet press	

Automatic High-Temp Heat Press

Item Number: PPL



Introduction

The Automatic High Temperature Heat Press is a sophisticated hydraulic hot press designed for efficient temperature control and product quality processing.

[Learn More](#)

Instrument model	PP-900L
Pressure Range	0-10T
Pressurization process	Program pressurization-program pressure-timed pressure relief
Pressure retention time	1 second ~ 90seconds
Cylinder stroke	80mm
Heatingtemperature	Upto 1000°C
Mold material	Nickel-based alloy (high temperature resistant material)
Sample size	Φ10-30mm
Mold shape	Φ50x90mm
The caliber of thefurnace	Φ60mm
Size of the whole machine	400x380x780(LxWxH)
power supply	220V 50Hz
Dimensional diagram of powder tablet press	

Manual Heat Press High Temperature Hot Pressing

Item Number: CPCL



Introduction

The Manual Heat Press is a versatile piece of equipment suitable for a variety of applications, operated by a manual hydraulic system that applies controlled pressure and heat to the material placed on the piston.

[Learn More](#)

Instrument model	PC-900L
Pressure Range	0-5.0 tons
Pressurization process	Manual pressurization
Cylinder stroke	80mm
Heating temperature	Up to 1000°C
Mold material	Nickel-based alloy (high temperature resistant material)
Sample size	Φ10-30mm
Mold shape	Φ50x90mm
The caliber of the furnace	Φ60mm
Size of the whale machine	400x380x780(LxWxH)
power supply	220V 50Hz

Dimensional diagram of powder tablet press

Manual High Temperature Heat Press

Item Number: PCHT



Introduction

The High Temperature Hot Press is a machine specifically designed for pressing, sintering and processing materials in a high temperature environment. It is capable of operating in the range of hundreds of degrees Celsius to thousands of degrees Celsius for a variety of high temperature process requirements.

[Learn More](#)

Instrument model	PCHT
Pressure range	0-5.0 tons
Pressure process	Manual pressurization
Pressure holding time	1 second ~ ∞ seconds
Cylinder stroke	80mm
Heating temperature	Maximum 1000°C
Mold material	Nickel-based alloy (high temperature resistant material)
Sample size	Medium 10-30mm
Mold shape	Medium 50x90mm
Furnace diameter	Medium 60mm
Complete machine size	400x380x780 (LxWxH)
Power supply	220V 50Hz
Powder tablet press size diagram	

Automatic High Temperature Heat Press Machine

Item Number: PHA



Introduction

The High Temperature Hot Press is a machine specifically designed for pressing, sintering and processing materials in a high temperature environment. It is capable of operating in the range of hundreds of degrees Celsius to thousands of degrees Celsius for a variety of high temperature process requirements.

[Learn More](#)

Instrument model	PHA
Pressure range	0-10T
Pressure process	Program pressurization-Program pressure maintenance-timed pressure release
Pressure holding time	1 second~∞ seconds
Cylinder stroke	80mm
Heating temperature	Maximum 1000°C
Mold material	Nickel-based alloy (high temperature resistant material)
Sample size	Medium 10-30mm
Mold shape	Medium 50*90mm
Furnace diameter	Medium 60mm
Complete machine size	400*380*780 (L*W*H)
Power supply	220V 50Hz
Powder tablet press size diagram	



Kintek Solution

Head Quarter: No.89 Science Avenue, High-Tech Zone,
Zhengzhou, China

