



KINTEK SOLUTION

Vacuum Furnace Catalog

Contact us for more catalogs of **Sample Preparation, Thermal Equipment, Lab Consumables & Materials, Bio-Chem Equipment, etc.**

KINTEK SOLUTION

COMPANY PROFILE

>>> About Us

Company Profile

Kintek Solution Ltd is one technology orientated organization, team members are devoted to probing the most efficient and reliable technology and innovations in the scientific researching equipment, fields like biochemical reacting, new materials researching, heat treatment, vacuum creating, refrigerating, as well as pharmaceutical and petroleum extracting equipment.

Products & Services

Kintek Solution Ltd is headquartered in Zhengzhou, the capital city of Henan Province, China, and its core business includes the manufacture, distribution and sale of all types of scientific research equipment and laboratory consumables. The wide range of products and services covers the following main areas:

- **Sample Preparation Equipment:** We provide high-performance sample preparation equipment such as tablet presses, ball mills, vibrating sieves and tablet punching machines, which are capable of meeting a wide range of sample preparation needs and ensuring high quality experimental data and research results.
- **Thermal Equipment:** Our thermal equipment includes tube furnaces, sintering furnaces, vacuum furnaces, atmosphere furnaces, graphite furnaces, dental furnaces, rotary furnaces, and high-temperature furnaces (e.g., MPCVD, CVD, PECVD, electric rotary kilns). These facilities excel in high-temperature processing and materials synthesis, meeting a wide range of needs from basic research to industrial production.
- **Biochemical equipment:** We offer a wide range of biochemical laboratory equipment, including rotary evaporators, vacuum pumps, cold trap chillers,

heating circulators, reactors, short-range distillation equipment, sterilization equipment, and homogenizers. These equipments are widely used in the fields of chemical reaction, biological processing and pharmaceutical manufacturing.

- **Laboratory Consumables:** We supply a wide range of laboratory consumables such as fine ceramic products, electrochemical consumables, PTFE material products, high purity materials, battery materials, chemical vapor deposition materials, optical materials, thin film deposition components and glass materials. These consumables provide the necessary support for laboratories to ensure the smooth running of experimental processes.

Technological Advantages

Kintek Solution Ltd has significant technological strengths in the field of scientific research equipment and technical solutions, which enable us to stand out in a competitive marketplace and support our customers with cutting-edge technology. The following are our key technological strengths:

Advanced R&D capabilities

- **Technological Innovation:** Our R&D team is committed to exploring and developing the latest technologies to keep our equipment at the forefront of the industry through continuous technological innovation.
- **Customized solutions:** Based on the specific needs of our customers, we are able to develop and provide customized equipment to meet specific research requirements and application scenarios.
- **Cooperative R&D:** We cooperate with leading research institutes and higher education institutions around the world to carry out R&D projects on cutting-edge technologies to ensure that our technologies are always at the forefront of the industry.

High-performance equipment

- **Precision design:** Our equipment adopts advanced design concepts to ensure high precision, reliability and performance to meet the stringent requirements of scientific research and industrial applications.
- **Advanced materials:** We use high-quality materials and components to improve the durability and stability of our equipment, extend its service life and reduce maintenance costs.

Strict quality control

- Standardized production: All equipment is manufactured in accordance with international quality standards, and each production step is strictly controlled to ensure product consistency and reliability.
- Comprehensive testing: Comprehensive performance testing and quality inspection are carried out before the equipment is delivered to ensure that it meets the customer's technical specifications and operational requirements.

Comprehensive technical support

- Technical Service: Provide comprehensive technical support and after-sales service, including equipment installation, commissioning, training and maintenance, to ensure that customers can use our products efficiently.
- Rapid Response: We have established a rapid response mechanism, which can promptly solve the problems encountered by customers in the process of use and reduce equipment downtime.

Innovative technology integration

- System Integration: We integrate advanced control systems and automation technologies into our equipment to improve operational efficiency and data accuracy, and streamline operational processes.

Through these technological advantages, Kintek Solution Ltd is able to continue to provide our customers with innovative, efficient and reliable scientific research equipment and solutions to promote the continuous progress of scientific research and industrial applications.

Market position and customers

Kintek Solution Ltd is positioned in the market as a leading global provider of high-tech research equipment and solutions, specializing in biochemical reactions, new materials research, heat treatment, vacuum manufacturing, refrigeration, as well as pharmaceuticals and oil extraction. We are committed to brand leadership in research equipment by providing innovative technology and high quality equipment to meet the needs of research organizations and industrial companies in complex research and production processes.

Core Market Positioning:

- **Specialization:** We focus on high technology and scientific research, providing advanced equipment and solutions for specialized research institutes, laboratories and industrial applications.
- **High-end customers:** Our main customers include world-renowned universities, research institutes and various industrial enterprises, which usually have high requirements for equipment performance and technology.
- **Technological Innovation:** We are committed to technological innovation and customized solutions to ensure that our customers receive cutting-edge technical support to meet the ever-changing needs and challenges in the market.

Market Customer Groups:

- **Research Institutes and Universities:** including the world's leading research institutes and institutions of higher learning, who require high-performance research equipment and technical support for basic research, applied research and technology development.
- **Industrial companies:** covering a wide range of industries such as pharmaceuticals, oil extraction, new materials manufacturing and electronic materials production, these companies rely on reliable equipment and solutions to ensure product quality and productivity during production.
- **Laboratories and test centers:** organizations that provide laboratory services and quality testing, requiring accurate laboratory equipment and instruments for sample analysis and testing.
- **Technology Development Companies:** Companies that specialize in the development and application of new technologies and have a high demand for innovative equipment and technical solutions to support their R&D projects and technology validation.

Through clear market positioning and customer groups, we are committed to promoting scientific and technological progress, supporting the innovation and development of our global customers, and continuing to provide high-quality products and services to the market.

Team Introduction

The team at Kintek Solution Ltd is at the heart of the company's success. In order to realize our vision and maintain our leadership position in the field of high-tech research equipment, we are committed to building an exceptional team with the following attributes:

1. Professionalism

- **Technical Expertise:** Our team consists of technical experts and engineers in the field with deep expertise and technical backgrounds to meet complex technical challenges and innovation needs.
- **Industry experience:** We bring together professionals with extensive experience in the fields of research equipment, material science and engineering technology to ensure a precise grasp of market needs and technological trends.

2. Innovative Spirit

- **R&D-driven:** The team encourages innovative thinking and technological exploration, supports employees to participate in R&D projects on cutting-edge technologies, and continuously pushes forward the technological advancement of products and solutions.
- **Flexible Adaptation:** In the face of changing market environment, we have the ability to adapt quickly and flexibly to meet the changing needs of our customers.

3. Collaboration and Communication

- **Cross-sectoral collaboration:** The team maintains close collaboration between various departments, including R&D, production, sales and customer service, to ensure the smooth progress of projects and timely response to customer needs.
- **Efficient Communication:** Emphasize internal communication and information sharing, through efficient communication mechanisms and tools to ensure that all team members are consistent with the project goals and progress.

4. Customer Orientation

- **Customer Service:** Team members are customer-focused and committed to providing quality service and support to ensure that our customers have the best experience in using our products and solutions.

- Customized solutions: the ability to deeply understand the specific needs of customers and provide customized solutions to meet the special requirements of different customers.

5. Professional Training and Development

- Continuous Learning: We provide continuous training and learning opportunities for our team members to ensure that they are always up-to-date with the latest technology and industry knowledge.
- Career Development: We value the career development and growth of our employees, provide clear career paths and promotion opportunities, and motivate our employees to realize their personal goals and career aspirations within the company.

6. Corporate Culture

- Integrity and Responsibility: The team upholds integrity and responsibility, treats work and customers with honesty and fairness, and builds trust and long-term cooperative relationships.
- Unity and Collaboration: Focusing on the spirit of teamwork, the team emphasizes mutual support and joint efforts to achieve the company's goals and promote the overall success of the team.

By building such a highly qualified, innovation-driven and customer-oriented team, we ensure that Kintek Solution Ltd continues to lead in the field of scientific research equipment and provide excellent products and services to our customers worldwide.

At KINTEK, technology fuels our corporate spirit. This dynamic energy awaits you upon joining our team. Expect a distinctive cultural environment where our global business focus opens doors to diverse customs and traditions worldwide. Here, challenging roles promise to propel your career to new heights.

Our exceptional corporate culture sparks innovation, fosters care, and drives continuous progress among individuals and teams. Our team embodies youthfulness, positivity, enthusiasm, and a bold attitude toward challenges. Passionate about our business, our employees ardently contribute to the company's growth.

We seek individuals brave enough to embrace challenges, harbor grand ambitions, and thirst for knowledge. If you're driven by dreams and passion, and aspire to start your

entrepreneurial journey, KINTEK is the platform to actualize your career plans. We don't just offer opportunities; we pave the way for your future.

Join us at KINTEK, where innovation meets opportunity. Let's create a future that's as promising as your aspirations.

Future Plans

Kintek Solution Ltd's future plans are aimed at further strengthening our leadership position in the research equipment sector and driving the company forward in terms of technological innovation, market expansion and customer service. The following are our key future directions:

1. Technology Innovation and R&D

- Cutting-edge technology development: Continue to invest resources in the research and development of cutting-edge technologies, such as artificial intelligence, the Internet of Things and nanotechnology, in order to promote equipment intelligence and automation.
- New Product Lines: Expand existing product lines and develop equipment to meet emerging market needs, especially in the areas of biochemistry, biomedicine and high-performance materials.
- Cooperative R&D: Strengthen cooperation with international research institutes and institutions of higher learning to carry out joint R&D projects to ensure that the technology remains at the global leading level.

2. Market Expansion

- Global Market Expansion: Further expand the global market, especially in emerging markets and developing regions, establish more sales and service networks, and enhance the brand's international influence.
- Industry application: Explore and expand the application fields in other industries, such as new energy, environmental protection technology and intelligent manufacturing, to open up new business growth points.

3. Customer Service Enhancement

- Enhancement of customer support: Establish a more complete customer support system, provide 24/7 technical support and maintenance services, and ensure

the efficient experience of customers in the use of equipment.

- Customized services: Provide more customized services and solutions according to customers' individual needs to enhance customer satisfaction and loyalty.

4. Sustainable Development

- Environmentally friendly technology: Develop and adopt environmentally friendly materials and processes to reduce the environmental impact during the production and use of equipment and promote sustainable development.
- Energy saving and consumption reduction: Optimize the energy efficiency of equipment, reduce energy consumption, improve resource utilization efficiency, and support the development of green technology.

5. Internal optimization

- Intelligent management: Implement intelligent management systems and data analysis tools to improve productivity and management and reduce operating costs.
- Employee Training: Enhance employee training and skills upgrading to build a high-quality team to meet changing market demands and technological challenges.

6. Innovation ecosystem

- Establishment of innovation platform: Create innovation platforms and laboratories to support employees and partners in technological innovation and product development.
- Industry Chain Cooperation: Deepen cooperation with the upstream and downstream of the industry chain, integrate resources, and promote the development and implementation of industry technical standards and market norms.

Through these future plans, Kintek Solution Ltd will continue to lead the forefront of science and technology, provide customers with more advanced and reliable products and services, and at the same time, promote the sustainable development of the enterprise and the progress of the industry.



Vacuum Furnace With Ceramic Fiber Liner

Item Number: KT-VF



Introduction

Vacuum furnace with polycrystalline ceramic fiber insulation liner for excellent heat insulation and uniform temperature field. Choose from 1200°C or 1700°C max. working temperature with high vacuum performance and precise temperature control.

[Learn More](#)

Furnace model	KT-VF12/KT-VF17
Max. temperature	1200/1700°C
Constant work temperature	1100/1600°C
Chamber material	Ceramic polycrystalline fiber
Heating element	Cr2Al2Mo2 wire coil/Molybdenum Disilicide
Heating rate	0-20°C/min
Temperature sensor	Build in K/B type thermal couple
Temperature controller	Touch screen PID controller with PLC
Temperature control accuracy	±1°C
Temperature uniformity	±5°C
Electric power supply	AC110-440V,50/60HZ

Standard Chamber Sizes Stocks			
Chamber size (mm)	Effective volume (L)	Chamber size (mm)	Effective volume (L)
100x100x100	1	400x400x500	80
150x150x200	4.5	500x500x600	125
200x200x300	12	600x600x700	253
300x300x400	36	800x800x800	512

Customer design sizes and volume is accepted

Molybdenum Vacuum Furnace

Item Number: KT-VM



Introduction

Discover the benefits of a high-configuration molybdenum vacuum furnace with heat shield insulation. Ideal for high-purity, vacuum environments like sapphire crystal growth and heat treatment.

[Learn More](#)

Furnace model	KT-VM
Max. temperature	1400 °C
Constant work temperature	1300 °C
Chamber insulation material	molybdenum heat shield
Heating element	Molybdenum Strip
Heating rate	0-10°C/min
Temperature sensor	Build in S type thermal couple
Temperature controller	Touch screen PID controller with PLC
Temperature control accuracy	±1°C
Temperature uniformity	±5°C
Electric power supply	AC110-440V,50/60HZ

Standard Chamber Sizes Stocks

Chamber size (mm)	Effective volume (L)	Chamber size (mm)	Effective volume (L)
150x150x200	4.5	400x400x500	80
200x200x300	12	500x500x600	125
300x300x400	36	600x600x700	253

Customer design sizes and volume is accepted

Furnace Chamber

- Regularly inspect the chamber's interior surface for brightness.
- Ensure dryness and cleanliness inside the chamber to prevent oxidation and product contamination.
- Avoid rapid heating rates that may cause thermal expansion deformation of the insulation screen.
- Verify the leak rate and ultimate vacuum before initiating heating.
- Maintain a vacuum in the chamber when not in use, and perform chamber baking if volatiles are present.
- Implement a slower heating rate during high-temperature stages.

<p>Molybdenum Strips Heater</p>	<ul style="list-style-type: none"> • Molybdenum Strips Heater • Take care not to drop objects onto the molybdenum strips when removing products, as it may cause breakage. • Prevent low-melting point iron-containing products from volatilizing onto the molybdenum strips, as it can lead to strip melting and breakage over time. • Securely hold the product with both hands or appropriate tools when taking it out. • Strictly control the impurity content in the product.
<p>Pirani Gauge and Ionisation Gauge</p>	<ul style="list-style-type: none"> • Adhere to safety regulations for electrical equipment when operating and maintaining pirani gauges. • Avoid forcibly disassembling the gauge tubes while the furnace is under vacuum. • Do not pressurize the gauge (above 0.05Pa); if necessary, turn off the gauge power. • Refrain from introducing corrosive gas atmospheres. • Calibrate the vacuum gauge with dry air or nitrogen, as other atmospheres may cause measurement deviations. • Avoid turning on the ionization gauge under atmospheric pressure, as it may result in damage. • Clean the seals and contact surfaces with acetone or alcohol when disassembling, and apply vacuum grease before reassembling. • Perform zero point and full-scale calibration for the first use or after a period of use to match the vacuum and pirani gauges.
<p>Mechanical Pump</p>	<ul style="list-style-type: none"> • Ensure the pump temperature does not exceed 45 degrees to prevent non-wear of the pump cavity and detrimental effects on the vacuum. • Monitor the oil color in the oil window regularly. • Check for oil splashing from the exhaust when starting the vacuum pump, and inspect the oil level. • Measure the pump temperature before and during operation, and monitor the cooling water temperature. • Change the oil every three months (model: HFV-100). • If the oil level is high, open the drain valve to lower it to the standard level.
<p>Roots Pump</p>	<ul style="list-style-type: none"> • Maintain cleanliness inside the pump cavity. • Monitor the quality of pump oil. • Ensure proper pump rotation. • Avoid placing products with high moisture or large particles in the furnace chamber. • Promptly replace the diffusion pump oil if it becomes discolored or emulsified. • Immediately contact the manufacturer if any abnormal conditions occur with the pump.
<p>Diffusion Pump</p>	<ul style="list-style-type: none"> • Check if the diffuser oil in the oil window requires replacement. • Monitor the pumping speed after starting. • Ensure adequate cooling water supply to the pump. • Replace the diffusion pump oil with the appropriate model (HFV-3). • Verify that the heater temperature, oil level, and pump core installation are normal. • Maintain the pump surface temperature between 10-35 degrees Celsius and humidity below 65%.
<p>Water Cooler</p>	<ul style="list-style-type: none"> • Thoroughly read the manual before operating the water cooler. • Pay attention to the rotation directions of the inlet and outlet water pumps. • Confirm that the furnace water inlet pressure is displayed correctly after starting. • Establish an effective heat dissipation system. • Regularly check the water quality inside the water tank. • Clean the heat dissipation system every 3-5 months. • Avoid overloading the set temperature; for example, if the set temperature is 20 degrees, it should not go below 21 degrees. Adjust the set point above 21 degrees. • Ensure proper ventilation for the cooler's placement. • Occasionally open the side cover and clean the inside water tank with diluted hydrochloric acid.

2200 °C Graphite Vacuum Furnace

Item Number: KT-VG



Introduction

Discover the power of the KT-VG Graphite Vacuum Furnace - with a maximum working temperature of 2200°C, it's perfect for vacuum sintering of various materials. Learn more now.

[Learn More](#)

Furnace model	KT-VG		
Max. temperature	2200 °C		
Constant work temperature	2100 °C		
Chamber insulation material	Graphite felt		
Heating element	Graphite resistant rod		
Heating rate	0-10°C/min		
Temperature sensor	T/R thermocouple and infrared thermometer		
Temperature controller	Touch screen PID controller with PLC		
Temperature control accuracy	±1°C		
Electric power supply	AC110-440V,50/60HZ		
Standard Chamber Sizes Stocks			
Chamber size (mm)	Effective volume (L)	Chamber size (mm)	Effective volume (L)
200x200x300	12	400x400x600	96
300x300x400	36	500x500x700	150
Customer design sizes and volume is accepted			

2200 °C Tungsten Vacuum Furnace

Item Number: KT-VT



Introduction

Experience the ultimate refractory metal furnace with our Tungsten vacuum furnace. Capable of reaching 2200°C, perfect for sintering advanced ceramics and refractory metals. Order now for high-quality results.

[Learn More](#)

Furnace model	KT-VT		
Max. temperature	2200 °C		
Constant work temperature	2100 °C		
Chamber insulation material	Tungsten heat shield		
Heating element	Tungsten coil/mesh		
Heating rate	0-10°C/min		
Temperature sensor	T/R thermocouple and infrared thermometer		
Temperature controller	Touch screen PID controller with PLC		
Temperature control accuracy	±1°C		
Electric power supply	AC110-440V,50/60HZ		
Standard Chamber Sizes			
Model	Chamber size	Temperature uniformity	Rated power
KT-VT1010	φ100x 100mm	±3°C	21Kw
KT-VT2030	φ200x 300mm		68Kw
KT-VT3050	φ300x 500mm		120Kw
KT-VT4060	φ400x 600mm		160Kw
Customer design sizes and volume is accepted			

Vacuum Induction Melting Furnace Arc Melting Furnace

Item Number: KT-VI



Introduction

Get precise alloy composition with our Vacuum Induction Melting Furnace. Ideal for aerospace, nuclear energy, and electronic industries. Order now for effective smelting and casting of metals and alloys.

[Learn More](#)

Crucible effective volume	4L
Crucible effective capacity (Steel)	20kgs
Max temperature	2000 °C
Max melting vacuum	<ul style="list-style-type: none"> • 7×10⁻³Pa • Vacuum time: open diffusion pump when preheating is complete, then up to 7×10⁻³Pa in 30 minutes.
Rated power	60KW
Rated voltage	375V
Power frequency	50HZ
Rated frequency	1500~2500HZ
Rated frequency	1500~2500HZ
Heat element	Induction copper coil
Vacuum system	<ul style="list-style-type: none"> • 70L/s Double stage Rotary vane mechanical pump • Dia.300mm diffusion pump, Max. pumping speed: 5000L/s • Dia.300mm diffusion pump clod trap, effective cooling cycle for pump oil • Dia.300mm diffusion pump flapper valve + Dia.80mm former pump flapper valve • Stainless pipe + stainless bellows

Model	Capacity	Temperature	Vacuum	Rated power
KT-VI5	5kg			40Kw
KT-VI10	10kg			40Kw
KT-VI25	25kg			75Kw
KT-VI50	50kg	1700 °C	6x10 ⁻³ Pa	100Kw
KT-VI100	100kg			160Kw
KT-VI200	200kg			200Kw
KT-VI500	500kg			500Kw

Semi-contentiously melting production can be customized

Vacuum Levitation Induction Melting Furnace

Item Number: KT-VIL



Introduction

Experience precise melting with our Vacuum Levitation Melting Furnace. Ideal for high melting point metals or alloys, with advanced technology for effective smelting. Order now for high-quality results.

[Learn More](#)

Model	KT-VIL-0.5	KT-VIL-2	KT-VIL-5	KT-VIL-10	KT-VIL-20
Capacity	0.5kg	2kg	5kg	10kg	20kg
Vacuum leakage	5Pa/h				
Vacuum pressure	6×10 ⁻³ Pa				
Power supply	380V[3phase]50Hz				
Frequency	6000-10000Hz				
Rated power	25kW	160kW	400kW	400kW	500kW
Cold water pressure	0.2-0.4MPa				
Cold water consumption	3M3	15M3	30M3	40M3	45M3

Vacuum Induction Melting Spinning System Arc Melting Furnace

Item Number: KT-VIS



Introduction

Develop metastable materials with ease using our Vacuum Melt Spinning System. Ideal for research and experimental work with amorphous and microcrystalline materials. Order now for effective results.

[Learn More](#)

Model	KT-VIS2	KT-VIS15	KT-VIS50	KT-VIS100
Capacity	20g	150g	500g	1000g
Crucible	Boron Nitride/Quartz			
Belt width	1-10mm	1-30mm	1-40mm	1-70mm
Spinner size	φ200mm	φ220mm	φ300mm	φ300mm
Speed	3000r/min			
Vacuum	6.7*10 ⁻⁴ pa			
Insert gas	Ar			
Rated power	7kw	15kw	25kw	35kw
Power supply	AC110-480V 50/60HZ			
Optional part	Infrared temperature meter, recirculating chiller, Spray casting copper mold			

Other requirement can be customized

Vacuum Arc Furnace Induction Melting Furnace

Item Number: KT-VA



Introduction

Discover the power of Vacuum Arc Furnace for melting active & refractory metals. High-speed, remarkable degassing effect, and free of contamination. Learn more now!

[Learn More](#)

Model	KT-VA1	KT-VA5	KT-VA25	KT-VA200
Capacity (Kg)	1	5-15	25	200
Working voltage (V)	20-40			
Working current (A)	1000A	3000A	6000A	12000A
Vacuum pressure (Pa)	1.3-1.3x10 ⁻²			
Electrode size (mm)	Φ25-40 x 400	Φ10-45x1200	Φ30-60x1350	Φ56-150x1745
Ingot size (mm)	Φ60x100	Φ80x135	Φ100x400mm	Φ200x670mm
Dimensions (m)	0.8x0.35x1.8	3.81x3.0x5.21	4.43x3.33x4.93	7.4x3.4x6.72

Non Consumable Vacuum Arc Furnace Induction Melting Furnace

Item Number: KT-VAN



Introduction

Explore the benefits of Non-Consumable Vacuum Arc Furnace with high melting point electrodes. Small, easy to operate & eco-friendly. Ideal for laboratory research on refractory metals & carbides.

[Learn More](#)

Melting temperature	3500 °C
Vacuum chamber	304 stainless steel
Vacuum pressure	
Melting capacity	20-500g
Rated melting current	200-1000A
Smelting station	5-7 standard smelting station
Insert working gas	Ar
Optional function	Suction casting/Extra smelting station

Vacuum Hot Press Furnace

Item Number: KT-VHP



Introduction

Discover the advantages of Vacuum Hot Press Furnace! Manufacture dense refractory metals & compounds, ceramics, and composites under high temp and pressure.

[Learn More](#)

Specification	<ul style="list-style-type: none"> The electric furnace is heated by a vertical furnace body (pressure ranges from 5-800T, and the pressurization method is divided into one-way and two-way). The feeding and discharging methods are divided into top and side. , electronic control system and other components.
Furnace shell	<ul style="list-style-type: none"> The furnace shell is a double-layer water-cooled structure, the inner layer is strictly polished stainless steel, the outer layer is stainless steel sandblasting matte treatment or carbon steel anti-rust treatment, water cooling is passed between the double layers, and the furnace shell does not exceed 60 °C. The furnace cover is lifted by a mechanical mechanism, manually rotated backwards to open (one-way pressure), and a locking device is installed on the furnace cover.
Stove side	<ul style="list-style-type: none"> The side of the furnace is equipped with an observation window, a thermocouple automatic entry and exit mechanism, an infrared thermometer and a water-cooled electrode (three-phase). The automatic entry and exit of the thermoelectric cell is electric, with high and low temperature automatic switching. In order to prevent accidents caused by abnormal furnace temperature, there is also an over-temperature protection thermocouple on the side of the furnace.
The heating element	<ul style="list-style-type: none"> The heating element is made of graphite tube (or molybdenum wire), which can be divided into single-phase and three-phase heating. The rational design of the heating element improves the uniformity of the furnace temperature.
The insulation layer	<ul style="list-style-type: none"> The insulation layer is made of graphite (or graphite paper), carbon felt, etc., which has good insulation performance, and the unique structural design reduces the vacuuming time. The insulation layer of the molybdenum wire hot pressing furnace is a metal reflective screen.
The vacuum system	<ul style="list-style-type: none"> The vacuum system consists of two-stage vacuum pumps, one oil diffusion pump and one mechanical pump to complete the high and low vacuum. The vacuum valve adopts the high-vacuum baffle valve designed and produced by our company, which can realize automatic switching and control of high and low vacuum with digital display vacuum gauge and PLC.
The main circuit of the electric control system	<ul style="list-style-type: none"> The main circuit of the electric control system is low-voltage and high-current input. The electric control cabinet is made with reference to the standard cabinet of Rittal. It is humanized design. There are graphic simulation screens and buttons on the control panel. The operation is intuitive and convenient. The temperature and pressure control are controlled by imported brand programs. Instrument, the cabinet is equipped with a PLC, and the sintering process is automatically completed near the preset program. The control system has sound and light alarm functions for abnormal phenomena such as water cut-off, over-temperature, over-current, and thermocouple automatic switching failure.
Working temperature	1500°C / 2200°C
Heating element	Molybdenum/Graphite
Working pressure	10-400T
Press distance	100-200mm
Vacuum pressure	6x10 ⁻³ Pa

Effective working area diameter range	90-600mm
Effective working area diameter range	120-600mm

Vacuum Lamination Press

Item Number: KT-VLP



Introduction

Experience clean and precise lamination with Vacuum Lamination Press. Perfect for wafer bonding, thin-film transformations, and LCP lamination. Order now!

[Learn More](#)

Dimensions	Over-all: 775mm(L) x 550mm(W) x 1325mm(H)
Structure	<ul style="list-style-type: none"> • Two 135 x 135 mm flat heating platens made of high temperature resistant Cr steel with max. working temperature of 500°C • 1000W Heating element is inserted into the center of the heating plates for fast heating • Max. Load on 135x135mm Heated Platen: 10 Metric Tons at 500°C (55 kg/cm²);20 Metric Tons at RT (110 kg/cm²) • Two precision temperature controllers which control two heating plates separately • with 30 programmable segments • Water cooling jackets are built on the both top & bottom of the heating plates for assisting cooling
Hydraulic Pump	<ul style="list-style-type: none"> • Modified electric hydraulic press is connected to vacuum chamber. • Movable distance between two heating plates: 15 mm. • Automatic max. pressure controlled via a digital pressure gauge. • Pressure accuracy: +/-0.01 Mpa (0.1 kg/cm²) • Two flat heating plates are installed with water cooling plates for Max. 500°C working temperature. • Water cooling (>15L/min) is required to cool the heating plates when the operating temperature is over 200 °C.
Temperature control and Pressure Display	<ul style="list-style-type: none"> • Two precision temperature controllers with 30 programmable segments control the heating plates . • separately with +/-1°C accuracy. • The temperature controllers have PID auto tune function, over-temperature protection and thermal couple broken protection. • Max. Temperature: 500°C with inert gas or vacuum with accuracy +/-1°C • Max. Heating rate: 2.5°C/min • Software and PC interface is built in the controller , which can be connected to a PC for computer controlling via a RS232 connector. • Digital pressure meter (controller) is built outside the vacuum chamber. • You can set pressure at the desired value which can stop the electric hydraulic press automatically.
Vacuum Chamber	<ul style="list-style-type: none"> • Electric hydraulic press and heating plates are placed inside then vacuum chamber. • Vacuum chamber is made of SS304 with the size: 525Lx480Wx450H (mm). • Vacuum chamber Capacity : about 75 Liters. • 300mm dia. vacuum sealed hinged type door with 150mm Dia. quartz glass window is installed for easy sample loading and observation. • Silicone O-ring can be used for all vacuum sealings . • One precision digital vacuum guage (10E-4 torr) is installed on the vacuum chamber .

Model	KT-VLP100	KT-VLP300	KT-VLP400
--------------	-----------	-----------	-----------

Heating plate size	100x100mm	300x300mm	400x400mm
Plates travel distance	30mm	40mm	40mm
Working pressure	30T during heating/40Tin the cold state		
Pressure gauge	Digital pressure gauge		
Heating temperature	<500°C		
Temperature control	Touch screen with PID thermal controller		
Vacuum chamber	304 Stainless steel		
Vacuum pump	Rotary vane vacuum pump		
Vacuum pressure	-0.1Mpa		
Power supply	AC110-220V, 50/60HZ		

Vacuum Tube Hot Press Furnace

Item Number: KT-VTP



Introduction

Reduce forming pressure & shorten sintering time with Vacuum Tube Hot Press Furnace for high-density, fine-grain materials. Ideal for refractory metals.

[Learn More](#)

Hydraulic press	Working pressure: 0-30Mpa Travel distance: <50mm Pressure stability: $\leq 1\text{MPa}/10\text{min}$ Pressure meter: Digital pressure gauge Drive solution: Electric drive with standby manual drive
Vertical split furnace	Working temperature: $\leq 1150^\circ\text{C}$ Heating element: Ni-Cr-Al resistance wire with dipped Mo Heating speed: $< 15^\circ\text{C}/\text{min}$ Hot zone length: 300mm Constant temperature zone: 100mm Controller: Touch screen with PID thermal controller Rated power: 2200W
Vacuum furnace tube	Tube material: Quartz tube(Optional Alumina/Nickel alloy) Tube diameter: 100mm(Optional 120/160mm) Vacuum sealing: SS flange with silicon O ring Flange cooling method: Inter layer water circulating cooling
Graphite pressing die	Die material: High purity graphite (Graphite must work under vacuum to prevent oxidation) Pressure rod diameter: 87mm Sleeve die size: 55mm OD/ 50mm Height Die inserts: OD22.8 x ID20.8 Pushing Rod: 12.7mmOD/40mm Height Other sizes die can be customer made
Vacuum pump setup	Rotary vane pump vacuum is up to 10 ⁻² torr Turbo pump station vacuum is up to 10 ⁻⁴ torr
Electric power supply	AC110-220V, 50/60HZ

Vacuum Pressure Sintering Furnace

Item Number: KT-VPS



Introduction

Vacuum pressure sintering furnaces are designed for high temperature hot pressing applications in metal and ceramic sintering. Its advanced features ensure precise temperature control, reliable pressure maintenance, and a robust design for seamless operation.

[Learn More](#)

Maximum temperature	2100°C
Pressure range	10-800T
Heating method	Graphite
Vacuum degree	6×10 ⁻³ Pa
Effective workspace	Customizable

600T Vacuum Induction Hot Press Furnace

Item Number: KT-VH



Introduction

Discover the 600T Vacuum Induction Hot Press Furnace, designed for high-temperature sintering experiments in vacuum or protected atmospheres. Its precise temperature and pressure control, adjustable working pressure, and advanced safety features make it ideal for nonmetal materials, carbon composites, ceramics, and metal powders.

[Learn More](#)

Maximum pressure	600T
Mold outer diameter	Ø680mm
Mold material	Graphite
Large sample size	Ø500mm
Cold vacuum degree	10Pa
Furnace body form	One for two
Heating method	Induction
Pressure method	Four-column mechanical pressurization

Vacuum Molybdenum Wire Sintering Furnace

Item Number: KT-VMW



Introduction

A vacuum molybdenum wire sintering furnace is a vertical or bedroom structure, which is suitable for withdrawal, brazing, sintering and degassing of metal materials under high vacuum and high temperature conditions. It is also suitable for dehydroxylation treatment of quartz materials.

[Learn More](#)

Temperature	1600°C
Working area size	Φ60×80 mm, Φ160×160 mm, Φ200×200 mm, Φ300×400 mm, Φ400×500 mm, etc.
Cold ultimate vacuum degree:	10 ⁻³ or 10 ⁻⁴ Pa
Pressure rise rate	≤3Pa/h
Power supply	Three-phase 380 V 50 Hz
Furnace temperature uniformity	±5 °C (under vacuum)
Loading and unloading methods	Upper or side or bottom
Automatic charging and discharging gas protection	Argon, nitrogen, hydrogen.
Control method	LCD touch screen and PLC as the core

Small Vacuum Tungsten Wire Sintering Furnace

Item Number: KT-VTW



Introduction

The small vacuum tungsten wire sintering furnace is a compact experimental vacuum furnace specially designed for universities and scientific research institutes. The furnace features a CNC welded shell and vacuum piping to ensure leak-free operation. Quick-connect electrical connections facilitate relocation and debugging, and the standard electrical control cabinet is safe and convenient to operate.

[Learn More](#)

9Mpa Air Pressure Sintering Furnace

Item Number: KT-APS



Introduction

The air pressure sintering furnace is a high-tech equipment commonly used for the sintering of advanced ceramic materials. It combines vacuum sintering and pressure sintering techniques to achieve high-density and high-strength ceramics.

[Learn More](#)

Air pressure sintering furnace	Vertical structure
The working area	Φ100×90mm, Φ200×220mm, etc.
The bottom-lift type	Φ300×400mm, etc.
The horizontal type	250×250×400mm, 375×375×475mm, etc.
Cold vacuum degree	10 ⁻³ Pa, 10Pa, etc
Maximum pressure	1.2MPa, 2MPa, 6MPa, 9MPa
Temperature	2000°C-2200°C

Vacuum Brazing Furnace

Item Number: KT-BF



Introduction

A vacuum brazing furnace is a type of industrial furnace used for brazing, a metalworking process that joins two pieces of metal using a filler metal that melts at a lower temperature than the base metals. Vacuum brazing furnaces are typically used for high-quality applications where a strong, clean joint is required.

[Learn More](#)

Rated power	100 Kw
Rated temperature	700 °C
Power supply	380 V, 50 Hz
Working area size	Φ820×1700□
Cold ultimate vacuum	6.67×10 ⁻³ Pa
Pressure rise rate	2pa/h
Temperature control accuracy	±1°C



Kintek Solution

Head Quarter: No.89 Science Avenue, High-Tech Zone,
Zhengzhou, China

